

- **Material:** stainless steel
- **Color:** silver

The foot has a protective gray EPDM rubber seal, which complies with strict hygiene regulations.

The static load mentioned is calculated on the center of the screw. In the case of vibrations or dynamic loads, these values are lower.

This system is developed for use in dairies, pharmaceutical and food industries, and factories that are subject to the strictest hygiene regulations.

The housing is equipped with a seal that, by its adhesion to the smooth surface of the screw, ensures that dirt does not enter.

Zvolená varianta

Název produktu	Stavitelná noha pro čisté provozy s vulkan. patkou ø80mm, M16x150mm, nerez
Kód	28242
Závit F	M16
Výška H1 (mm)	188
Regulace zdvíhu (mm)	65
Výška H2 (mm)	123
Průměr patky D (mm)	80
Hmotnost (g)	527
Výška A (mm)	38
Výška patky G (mm)	25
Statické zatížení (N)	10000
Klíč SW	17/20
Průměr D1 (mm)	24
Výška B (mm)	150

Varianty produktu

Název produktu	Kód	QTY	Závit F	Výška H1 (mm)	Regulace zdvíhu (mm)	Výška H2 (mm)	Průměr patky D (mm)	Hmotnost (g)	Výška A (mm)	Výška patky G (mm)	Statické zatížení (N)	Klíč SW	Průměr D1 (mm)
----------------	-----	-----	---------	---------------	----------------------	---------------	---------------------	--------------	--------------	--------------------	-----------------------	---------	----------------

Stavitelná noha pro čisté proozy s vulkan. patkou ø60mm, M16x125mm, nerez	28239	6	M16	160	40	95	60	412	35	22	7000	17/20	24
Stavitelná noha pro čisté proozy s vulkan. patkou ø60mm, M20x150mm, nerez	28240	0	M20	185	65	121	60	655	35	22	7000	17/26	30
Stavitelná noha pro čisté proozy s vulkan. patkou ø80mm, M16x150mm, nerez	28242	0	M16	188	65	123	80	527	38	25	10000	17/20	24
Stavitelná noha pro čisté proozy s vulkan. patkou ø80mm, M16x125mm, nerez	28241	0	M16	163	40	98	80	494	38	25	10000	17/20	24
Stavitelná noha pro čisté proozy s vulkan. patkou ø100mm, M16x150mm, nerez	28245	0	M16	191	65	128	100	691	41	28	15000	17/20	24

Stavitelná noha pro čisté proozy s vulkan. patkou ø80mm, M20x200mm, nerez	28244	0	M20	238	65	173	80	839	38	25	10000	17/26	30
Stavitelná noha pro čisté proozy s vulkan. patkou ø80mm, M20x150mm, nerez	28243	0	M20	188	65	123	80	737	38	25	10000	17/26	30
Stavitelná noha pro čisté proozy s vulkan. patkou ø100mm, M30x150mm, nerez	28248	0	M30	195	65	130	100	1467	43	28	15000	26/36	42
Stavitelná noha pro čisté proozy s vulkan. patkou ø100mm, M20x150mm, nerez	28246	0	M20	191	65	128	100	901	41	28	15000	17/26	30
Stavitelná noha pro čisté proozy s vulkan. patkou ø100mm, M24x150mm, nerez	28247	0	M24	192	65	129	100	1092	42	28	15000	20/30	35

Stavitelná noha pro čisté proozy s vulkan. patkou ø100mm, M20x200mm, nerez	28249	0	M20	241	65	176	100	1003	41	28	15000	17/26	30
Stavitelná noha pro čisté proozy s vulkan. patkou ø100mm, M30x200mm, nerez	28251	0	M30	245	65	180	100	1692	43	28	15000	26/36	42
Stavitelná noha pro čisté proozy s vulkan. patkou ø120mm, M16x150mm, nerez	28252	0	M16	195	65	130	120	1040	-	32	30000	17/20	-
Stavitelná noha pro čisté proozy s vulkan. patkou ø100mm, M24x200mm, nerez	28250	0	M24	242	65	179	100	1239	42	28	15000	20/30	35
Stavitelná noha pro čisté proozy s vulkan. patkou ø100mm, M30x150mm, nerez	28255	0	M30	199	65	134	120	1816	-	32	30000	26/36	-

Stavitelná noha pro čisté proozy s vulkan. patkou ø120mm, M20x150mm, nerez	28253	0	M20	195	65	130	120	1250	-	32	30000	17/26	-
Stavitelná noha pro čisté proozy s vulkan. patkou ø120mm, M24x150mm, nerez	28254	0	M24	196	65	131	120	1441	-	32	30000	20/30	-
Stavitelná noha pro čisté proozy s vulkan. patkou ø120mm, M30x200mm, nerez	28258	0	M30	249	65	184	120	2041	-	32	30000	26/36	-
Stavitelná noha pro čisté proozy s vulkan. patkou ø120mm, M20x200mm, nerez	28256	0	M20	245	65	180	120	1352	-	32	30000	17/26	-
Stavitelná noha pro čisté proozy s vulkan. patkou ø120mm, M24x200mm, nerez	28257	0	M24	246	65	181	120	1588	-	32	30000	20/30	-

Stavitelná noha pro čisté proozy s vulkan. patkou ø60mm, M16x150mm, nerez	27524	13	M16	185	65	120	60	445	35	22	7000	17/20	24
--	-------	----	-----	-----	----	-----	----	-----	----	----	------	-------	----