

- **Foot material:** Thermoplastic with glass fibers
- **Screw material:** Galvanized steel
- **Foot color:** Black

The static load, mentioned below in the parameters, is calculated on the center of the screw. In the case of vibrations or dynamic loads, these values are reduced.

You can order [a special anti-slip pad](#) for this product.

## Variants

Product name	Product code	QTY	Foot height G (mm)	Pitch K (mm)	Static load (N)	Thread F	SW key	Foot diameter D (mm)	Height without washer H (mm)	Screw length B (mm)	Height with washer H1 (mm)	Height A (mm)	Hole diameter L (mm)
Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-steel	13915	8	32	73	20000	M16	16	103	101	50	104	51	12,5
Adjustable leg with foot ø103mm and holes for anchoring, PA+GF-steel	13916	8	32	73	20000	M16	16	103	151	100	154	51	12,5
Adjustable leg with foot ø103mm and holes for anchoring, PA+GF-steel	13917	8	32	73	20000	M16	16	103	201	150	204	51	12,5

Product name	Product code	QTY	Foot height G (mm)	Pitch K (mm)	Static load (N)	Thread F	SW key	Foot diameter D (mm)	Height without washer H (mm)	Screw length B (mm)	Height with washer H1 (mm)	Height A (mm)	Hole diameter L (mm)
Adjustable foot with foot o103mm and holes for anchoring, PA+GF-steel	13918	8	32	73	20000	M16	16	103	251	200	254	51	12,5
Adjustable foot with foot o103mm and holes for anchoring, PA+GF-steel	14397	8	32	73	25000	M20	20	103	126	75	129	51	12,5
Adjustable foot with foot o103mm and holes for anchoring, PA+GF-steel	14398	8	32	73	25000	M20	20	103	151	100	154	51	12,5
Adjustable foot with foot o103mm and holes for anchoring, PA+GF-steel	14399	8	32	73	25000	M20	20	103	176	125	179	51	12,5

Product name	Product code	QTY	Foot height G (mm)	Pitch K (mm)	Static load (N)	Thread F	SW key	Foot diameter D (mm)	Height without washer H (mm)	Screw length B (mm)	Height with washer H1 (mm)	Height A (mm)	Hole diameter L (mm)
Adjustable foot with foot o103mm and holes for anchoring, PA+GF-steel	14400	8	32	73	25000	M20	20	103	201	150	204	51	12,5
Adjustable foot with foot o103mm and holes for anchoring, PA+GF-steel	14401	0	32	73	25000	M20	20	103	226	175	229	51	12,5
Adjustable foot with foot o103mm and holes for anchoring, PA+GF-steel	14402	0	32	73	25000	M20	20	103	251	200	254	51	12,5
Adjustable foot with foot o103mm and holes for anchoring, PA+GF-steel	14403	0	32	73	25000	M20	20	103	276	225	279	51	12,5