

- **Foot material:** thermoplastic with glass fibers
- **Screw material:** stainless steel
- **Foot color:** black

The static load, mentioned below in the parameters, is calculated on the center of the screw. In the case of vibrations or dynamic loads, these values are reduced.

You can additionally order [a special anti-slip pad](#) for this product.

Selected variant

Product name	Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel
Product code	13935
Foot height G (mm)	27
Height A (mm)	41
Foot diameter D (mm)	83
SW key	13
Height with washer H1 (mm)	244
Thread F	M16
Screw length B (mm)	200
Pitch K (mm)	55
Static load (N)	20000
Hole diameter L (mm)	8,5
Height without washer H (mm)	241

Variants

Product name	Product code	QTY	Foot height G (mm)	Height A (mm)	Foot diameter D (mm)	SW key	Height with washer H1 (mm)	Thread F	Screw length B (mm)	Pitch K (mm)	Static load (N)	Hole diameter L (mm)	Height without washer H (mm)

Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13849	0	27	38	83	14	91	M10	50	55	15000	8,5	88
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-stainless steel	13850	0	27	38	83	14	116	M10	75	55	15000	8,5	113
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13851	0	27	38	83	14	141	M10	100	55	15000	8,5	138
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13852	0	27	38	83	14	166	M10	125	55	15000	8,5	163
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13853	0	27	38	83	14	91	M12	50	55	15000	8,5	88

Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13854	0	27	38	83	14	116	M12	75	55	15000	8,5	113
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13855	0	27	38	83	14	141	M12	100	55	15000	8,5	138
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13856	0	27	38	83	14	166	M12	125	55	15000	8,5	163
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13857	0	27	38	83	14	91	M14	50	55	20000	8,5	88
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13858	0	27	38	83	14	116	M14	75	55	20000	8,5	113

Nastavitelná noha s pätkou ø83 mm a otvory pro kotvení, PA+GF-nerez	13859	0	27	38	83	14	141	M14	100	55	20000	8,5	138
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13860	0	27	38	83	14	166	M14	125	55	20000	8,5	163
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13861	0	27	38	83	14	191	M14	150	55	20000	8,5	188
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13862	0	27	38	83	14	216	M14	175	55	20000	8,5	213
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	14412	0	27	41	83	17	144	M20	100	55	20000	8,5	141

Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13929	0	27	41	83	13	94	M16	50	55	20000	8,5	91
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13930	0	27	41	83	13	119	M16	75	55	20000	8,5	116
Adjustable leg with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13931	0	27	41	83	13	144	M16	100	55	20000	8,5	141
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13932	0	27	41	83	13	169	M16	125	55	20000	8,5	166
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13933	0	27	41	83	13	194	M16	150	55	20000	8,5	191

Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13934	0	27	41	83	13	219	M16	175	55	20000	8,5	216
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13935	0	27	41	83	13	244	M16	200	55	20000	8,5	241
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	14411	0	27	41	83	17	119	M20	75	55	20000	8,5	116
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	14413	0	27	41	83	17	169	M20	125	55	20000	8,5	166
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	14414	0	27	41	83	17	194	M20	150	55	20000	8,5	191

Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	14415	0	27	41	83	17	219	M20	175	55	20000	8,5	216
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	14416	0	27	41	83	17	244	M20	200	55	20000	8,5	241
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	14417	0	27	41	83	17	269	M20	225	55	20000	8,5	266
Nastavitelná noha s pätkou ø83 mm a otvory pro kotvení, PA+GF-nerez	28399	0	18	30	83	10	180	M12	150	55	13000	54	177