

- **Foot material:** Thermoplastic with glass fibers
- **Screw material:** Galvanized steel
- **Foot color:** Black

Static The load, mentioned below in the parameters, is calculated on the center of the screw. In the case of vibrations or dynamic loads, these values are reduced.

You can order a [special anti-slip pad](#) for this product.

Selected variant

| | |
|-------------------------------------|--|
| Product name | Adjustable foot with foot ø65mm, PA+GF-steel |
| Product code | 13788 |
| Height with washer H1 (mm) | 86 |
| Thread F | M10 |
| Screw length B (mm) | 50 |
| Height without washer H (mm) | 83 |
| Static load (N) | 11000 |
| Height A (mm) | 33 |
| SW key | 14 |
| Foot diameter D (mm) | 65 |
| Foot height G (mm) | 23 |

Variants

| Product name | Product code | QTY | Height with washer H1 (mm) | Thread F | Screw length B (mm) | Height without washer H (mm) | Static load (N) | Height A (mm) | SW key | Foot diameter D (mm) | Foot height G (mm) |
|--|--------------|-----|----------------------------|----------|---------------------|------------------------------|-----------------|---------------|--------|----------------------|--------------------|
| Adjustable foot with foot ø65mm, PA+GF-steel | 13788 | 33 | 86 | M10 | 50 | 83 | 11000 | 33 | 14 | 65 | 23 |

| Product name | Product code | QTY | Height with washer H1 (mm) | Thread F | Screw length B (mm) | Height without washer H (mm) | Static load (N) | Height A (mm) | SW key | Foot diameter D (mm) | Foot height G (mm) |
|--|--------------|-----|----------------------------|----------|---------------------|------------------------------|-----------------|---------------|--------|----------------------|--------------------|
| Adjustable foot with foot o65mm, PA+GF-steel | 13789 | 16 | 111 | M10 | 75 | 108 | 11000 | 33 | 14 | 65 | 23 |
| Adjustable foot with foot o65mm, PA+GF-steel | 13790 | 19 | 136 | M10 | 100 | 133 | 11000 | 33 | 14 | 65 | 23 |
| Adjustable foot with foot o65mm, PA+GF-steel | 13791 | 15 | 161 | M10 | 125 | 158 | 11000 | 33 | 14 | 65 | 23 |
| Adjustable foot with foot o65mm, PA+GF-steel | 13792 | 14 | 86 | M12 | 50 | 83 | 11000 | 33 | 14 | 65 | 23 |
| Adjustable foot with foot o65mm, PA+GF-steel | 13793 | 10 | 111 | M12 | 75 | 108 | 11000 | 33 | 14 | 65 | 23 |
| Adjustable foot with foot o65mm, PA+GF-steel | 13794 | 5 | 136 | M12 | 100 | 133 | 11000 | 33 | 14 | 65 | 23 |
| Adjustable foot with foot o65mm, PA+GF-steel | 13795 | 12 | 161 | M12 | 125 | 158 | 11000 | 33 | 14 | 65 | 23 |

| Product name | Product code | QTY | Height with washer H1 (mm) | Thread F | Screw length B (mm) | Height without washer H (mm) | Static load (N) | Height A (mm) | SW key | Foot diameter D (mm) | Foot height G (mm) |
|--|--------------|-----|----------------------------|----------|---------------------|------------------------------|-----------------|---------------|--------|----------------------|--------------------|
| Adjustable foot with foot o65mm, PA+GF-steel | 13796 | 10 | 86 | M14 | 50 | 83 | 15000 | 33 | 14 | 65 | 23 |
| Adjustable foot with foot o65mm, PA+GF-steel | 13797 | 10 | 111 | M14 | 75 | 108 | 15000 | 33 | 14 | 65 | 23 |
| Adjustable foot with foot o65mm, PA+GF-steel | 13798 | 10 | 136 | M14 | 100 | 133 | 15000 | 33 | 14 | 65 | 23 |
| Adjustable foot with foot o65mm, PA+GF-steel | 13799 | 13 | 161 | M14 | 125 | 158 | 15000 | 33 | 14 | 65 | 23 |
| Adjustable foot with foot o65mm, PA+GF-steel | 13800 | 14 | 186 | M14 | 150 | 183 | 15000 | 33 | 14 | 65 | 23 |
| Adjustable foot with foot o65mm, PA+GF-steel | 13801 | 0 | 211 | M14 | 175 | 208 | 15000 | 33 | 14 | 65 | 23 |