

- **Foot material:** galvanized steel + vulcanized rubber NBR 80 Shore
- **Screw material:** galvanized steel C40
- **Foot color:** silver + black

The mentioned static load is calculated on the center of the screw. In the case of vibrations or dynamic loads, these values are lower.

## Selected variant

|                             |   |
|-----------------------------|---|
| <b>Product name</b>         | Adjustable foot with vulcan. foot ø120 mm, galvanized steel |
| <b>Product code</b>         | 14380   |
| <b>Height A (mm)</b>        | 42,5  |
| <b>Height H (mm)</b>        | 142,5   |
| <b>SW key</b>               | 24  |
| <b>Foot diameter D (mm)</b> | 120   |
| <b>Screw length B (mm)</b>  | 100   |
| <b>Static load (N)</b>      | 30000   |
| <b>Foot height G (mm)</b>   | 32  |
| <b>Thread F</b>             | M24   |

## Variants

| Product name   | Product code | QTY | Height A (mm) | Height H (mm) | SW key | Foot diameter D (mm) | Screw length B (mm) | Static load (N) | Foot height G (mm) | Thread F |
|--|--------------|-----|---------------|---------------|--------|----------------------|---------------------|-----------------|--------------------|----------|
| Adjustable leg with vulcan. foot ø120 mm, galvanized steel     | 14371        | 5   | 41,5          | 116,5         | 16     | 120                  | 75                  | 30000           | 32                 | M16      |
| Adjustable foot with vulcanized foot ø120 mm, galvanized steel | 14372        | 22  | 41,5          | 141,5         | 16     | 120                  | 100                 | 30000           | 32                 | M16      |

| Product name   | Product code | QTY | Height A (mm) | Height H (mm) | SW key | Foot diameter D (mm) | Screw length B (mm) | Static load (N) | Foot height G (mm) | Thread F |
|--|--------------|-----|---------------|---------------|--------|----------------------|---------------------|-----------------|--------------------|----------|
| Adjustable leg with vulcan. foot ø120 mm, galvanized steel     | 14373        | 6   | 41,5          | 191,5         | 16     | 120                  | 150                 | 30000           | 32                 | M16      |
| Adjustable foot with vulcanized foot ø120 mm, galvanized steel | 14374        | 2   | 41,5          | 241,5         | 16     | 120                  | 200                 | 30000           | 32                 | M16      |
| Adjustable foot with vulcan. foot ø120 mm, galvanized steel    | 14375        | 5   | 42,5          | 117,5         | 20     | 120                  | 75                  | 30000           | 32                 | M20      |
| Adjustable leg with vulcan. foot ø120 mm, galvanized steel     | 14376        | 0   | 42,5          | 142,5         | 20     | 120                  | 100                 | 30000           | 32                 | M20      |
| Adjustable foot with vulcan. foot ø120 mm, galvanized steel    | 14377        | 0   | 42,5          | 192,5         | 20     | 120                  | 150                 | 30000           | 32                 | M20      |
| Adjustable foot with vulcan. foot ø120 mm, galvanized steel    | 14378        | 0   | 42,5          | 242,5         | 20     | 120                  | 200                 | 30000           | 32                 | M20      |
| Adjustable foot with vulcan. foot ø120 mm, galvanized steel    | 14379        | 0   | 42,5          | 292,5         | 20     | 120                  | 250                 | 30000           | 32                 | M20      |
| Adjustable foot with vulcan. foot ø120 mm, galvanized steel    | 14380        | 10  | 42,5          | 142,5         | 24     | 120                  | 100                 | 30000           | 32                 | M24      |

| Product name  | Product code | QTY | Height A (mm) | Height H (mm) | SW key | Foot diameter D (mm) | Screw length B (mm) | Static load (N) | Foot height G (mm) | Thread F |
|---|--------------|-----|---------------|---------------|--------|----------------------|---------------------|-----------------|--------------------|----------|
| Adjustable foot with vulcan. foot ø120 mm, galvanized steel   | 14381        | 0   | 42,5          | 192,5         | 24     | 120                  | 150                 | 30000           | 32                 | M24      |
| Adjustable foot with vulcan. foot ø120 mm, galvanized steel   | 14382        | 5   | 42,5          | 242,5         | 24     | 120                  | 200                 | 30000           | 32                 | M24      |
| Adjustable leg with vulcan. foot ø120 mm, galvanized steel    | 14383        | 0   | 42,5          | 292,5         | 24     | 120                  | 250                 | 30000           | 32                 | M24      |
| Adjustable leg with vulcanized foot ø120 mm, galvanized steel | 14384        | 11  | 43,5          | 143,5         | 30     | 120                  | 100                 | 30000           | 32                 | M30      |
| Adjustable foot with vulcan. foot ø120 mm, galvanized steel   | 14385        | 0   | 43,5          | 193,5         | 30     | 120                  | 150                 | 30000           | 32                 | M30      |
| Adjustable foot with vulcan. foot ø120 mm, galvanized steel   | 14386        | 0   | 43,5          | 243,5         | 30     | 120                  | 200                 | 30000           | 32                 | M30      |
| Adjustable foot with vulcan. foot ø120 mm, galvanized steel   | 14387        | 0   | 43,5          | 293,5         | 30     | 120                  | 250                 | 30000           | 32                 | M30      |