

- **Foot material:** galvanized steel + vulcanized rubber NBR 80 Shore
- **Screw material:** galvanized steel C40
- **Foot color:** silver + black

The static load mentioned is calculated at the center of the screw. In the case of vibrations or dynamic loads, these values are lower.

Selected variant

Product name	Adjustable leg with vulcan. foot ø120 mm, galvanized steel
Product code	14383
Height A (mm)	42,5
Height H (mm)	292,5
SW key	24
Foot diameter D (mm)	120
Screw length B (mm)	250
Static load (N)	30000
Foot height G (mm)	32
Thread F	M24

Variants

Product name	Product code	QTY	Height A (mm)	Height H (mm)	SW key	Foot diameter D (mm)	Screw length B (mm)	Static load (N)	Foot height G (mm)	Thread F
Adjustable leg with vulcan. foot ø120 mm, galvanized steel	14371	5	41,5	116,5	16	120	75	30000	32	M16
Adjustable foot with vulcanized foot ø120 mm, galvanized steel	14372	22	41,5	141,5	16	120	100	30000	32	M16

Product name	Product code	QTY	Height A (mm)	Height H (mm)	SW key	Foot diameter D (mm)	Screw length B (mm)	Static load (N)	Foot height G (mm)	Thread F
Adjustable leg with vulcan. foot ø120 mm, galvanized steel	14373	6	41,5	191,5	16	120	150	30000	32	M16
Adjustable foot with vulcanized foot ø120 mm, galvanized steel	14374	2	41,5	241,5	16	120	200	30000	32	M16
Adjustable foot with vulcan. foot ø120 mm, galvanized steel	14375	5	42,5	117,5	20	120	75	30000	32	M20
Adjustable leg with vulcan. foot ø120 mm, galvanized steel	14376	0	42,5	142,5	20	120	100	30000	32	M20
Adjustable foot with vulcan. foot ø120 mm, galvanized steel	14377	0	42,5	192,5	20	120	150	30000	32	M20
Adjustable foot with vulcan. foot ø120 mm, galvanized steel	14378	0	42,5	242,5	20	120	200	30000	32	M20
Adjustable foot with vulcan. foot ø120 mm, galvanized steel	14379	0	42,5	292,5	20	120	250	30000	32	M20
Adjustable foot with vulcan. foot ø120 mm, galvanized steel	14380	10	42,5	142,5	24	120	100	30000	32	M24

Product name	Product code	QTY	Height A (mm)	Height H (mm)	SW key	Foot diameter D (mm)	Screw length B (mm)	Static load (N)	Foot height G (mm)	Thread F
Adjustable foot with vulcan. foot ø120 mm, galvanised steel	14381	0	42,5	192,5	24	120	150	30000	32	M24
Adjustable foot with vulcan. foot ø120 mm, galvanized steel	14382	5	42,5	242,5	24	120	200	30000	32	M24
Adjustable leg with vulcan. foot ø120 mm, galvanized steel	14383	0	42,5	292,5	24	120	250	30000	32	M24
Adjustable leg with vulcanized foot ø120 mm, galvanized steel	14384	11	43,5	143,5	30	120	100	30000	32	M30
Adjustable foot with vulcan. foot ø120 mm, galvanised steel	14385	0	43,5	193,5	30	120	150	30000	32	M30
Adjustable foot with vulcan. foot ø120 mm, galvanized steel	14386	0	43,5	243,5	30	120	200	30000	32	M30
Adjustable foot with vulcan. foot ø120 mm, galvanised steel	14387	0	43,5	293,5	30	120	250	30000	32	M30