

- **Foot material:** galvanized steel + vulcanized rubber NBR 80 Shore
- **Screw material:** galvanized steel C40
- **Foot color:** silver + black

The static load, mentioned below in the parameters, is calculated at the center of the screw. In the case of vibrations or dynamic loads, these values are reduced.

## Selected variant

|                             |                                                              |
|-----------------------------|--------------------------------------------------------------|
| <b>Product name</b>         | Adjustable foot with vulcanized foot ø60mm, galvanized steel |
| <b>Product code</b>         | 14320                                                        |
| <b>Thread F</b>             | M12                                                          |
| <b>Foot diameter D (mm)</b> | 60                                                           |
| <b>Height A (mm)</b>        | 32                                                           |
| <b>Foot height G (mm)</b>   | 22                                                           |
| <b>SW key</b>               | 14                                                           |
| <b>Height H (mm)</b>        | 182                                                          |
| <b>Static load (N)</b>      | 7000                                                         |
| <b>Screw length B (mm)</b>  | 150                                                          |

## Variants

| Product name                                                | Product code | QTY | Thread F | Foot diameter D (mm) | Height A (mm) | Foot height G (mm) | SW key | Height H (mm) | Static load (N) | Screw length B (mm) |
|-------------------------------------------------------------|--------------|-----|----------|----------------------|---------------|--------------------|--------|---------------|-----------------|---------------------|
| Adjustable foot with vulcan. foot ø60mm, galvanised steel   | 14316        | 11  | M10      | 60                   | 32            | 22                 | 14     | 82            | 7000            | 50                  |
| Adjustable leg with vulcanized foot ø60mm, galvanized steel | 14317        | 18  | M10      | 60                   | 32            | 22                 | 14     | 132           | 7000            | 100                 |

| Product name                                                               | Product code | QTY | Thread F | Foot diameter D (mm) | Height A (mm) | Foot height G (mm) | SW key | Height H (mm) | Static load (N) | Screw length B (mm) |
|----------------------------------------------------------------------------|--------------|-----|----------|----------------------|---------------|--------------------|--------|---------------|-----------------|---------------------|
| Adjustable foot with vulcanized foot ø60mm, galvanized steel               | 14318        | 0   | M12      | 60                   | 32            | 22                 | 14     | 82            | 7000            | 50                  |
| Adjustable leg with vulcan. foot Ø60mm, screw M12x100mm, galvanized. steel | 14319        | 4   | M12      | 60                   | 32            | 22                 | 14     | 132           | 7000            | 100                 |
| Adjustable foot with vulcanized foot ø60mm, galvanized steel               | 14320        | 2   | M12      | 60                   | 32            | 22                 | 14     | 182           | 7000            | 150                 |
| Adjustable foot with vulcanized foot ø60mm, galvanized steel               | 14321        | 0   | M14      | 60                   | 32            | 22                 | 14     | 82            | 7000            | 50                  |
| Adjustable foot with vulcan. foot ø60mm, galvanized steel                  | 14322        | 0   | M14      | 60                   | 32            | 22                 | 14     | 132           | 7000            | 100                 |
| Adjustable foot with vulcan. foot ø60mm, galvanized steel                  | 14323        | 0   | M14      | 60                   | 32            | 22                 | 14     | 182           | 7000            | 150                 |
| Adjustable foot with vulcan. foot ø60mm, galvanized steel                  | 14324        | 5   | M16      | 60                   | 32            | 22                 | 16     | 107           | 7000            | 75                  |
| Adjustable foot with vulcan. foot ø60mm, galvanized steel                  | 14325        | 30  | M16      | 60                   | 32            | 22                 | 16     | 132           | 7000            | 100                 |
| Adjustable foot with vulcanized with foot ø60mm, galvanized. steel         | 14326        | 6   | M16      | 60                   | 32            | 22                 | 16     | 182           | 7000            | 150                 |

| Product name                                                 | Product code | QTY | Thread F | Foot diameter D (mm) | Height A (mm) | Foot height G (mm) | SW key | Height H (mm) | Static load (N) | Screw length B (mm) |
|--------------------------------------------------------------|--------------|-----|----------|----------------------|---------------|--------------------|--------|---------------|-----------------|---------------------|
| Adjustable foot with vulcanized foot ø60mm, galvanised steel | 14327        | 2   | M16      | 60                   | 32            | 22                 | 16     | 232           | 7000            | 200                 |
| Adjustable foot with vulcan. foot ø60mm, galvanized steel    | 14328        | 5   | M20      | 60                   | 32            | 22                 | 20     | 108           | 7000            | 75                  |
| Adjustable foot with vulcan. foot ø60mm, galvanized steel    | 14329        | 0   | M20      | 60                   | 32            | 22                 | 20     | 133           | 7000            | 100                 |
| Adjustable foot with vulcan. foot ø60mm, galvanized steel    | 14330        | 0   | M20      | 60                   | 32            | 22                 | 20     | 183           | 7000            | 150                 |
| Adjustable foot with vulcanized foot ø60mm, galvanized steel | 14331        | 0   | M20      | 60                   | 32            | 22                 | 20     | 233           | 7000            | 200                 |
| Adjustable foot with vulcan. foot ø60mm, galvanized. steel   | 14332        | 0   | M20      | 60                   | 32            | 22                 | 20     | 283           | 7000            | 250                 |