

- **Materiál patky:** Termoplast se skleněnými vlákny
- **Materiál šroub:** Pozinkovaná ocel
- **Barva patky:** Černá

Statické zatížení, zmíněné níže v parametrech, je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

K tomuto výrobku si můžete přiojednat [speciální protiskluzovou podložku](#).

Selected variant

Product name	Adjustable leg with foot ø103mm and holes for anchoring, PA+GF-steel
Product code	13917
Foot height G (mm)	32
Pitch K (mm)	73
Static load (N)	20000
Thread F	M16
SW key	16
Foot diameter D (mm)	103
Height without washer H (mm)	201
Screw length B (mm)	150
Height with washer H1 (mm)	204
Height A (mm)	51
Hole diameter L (mm)	12,5

Variants

Product name	Product code	QTY	Foot height G (mm)	Pitch K (mm)	Static load (N)	Thread F	SW key	Foot diameter D (mm)	Height without washer H (mm)	Screw length B (mm)	Height with washer H1 (mm)	Height A (mm)	Hole diameter L (mm)
--------------	--------------	-----	--------------------	--------------	-----------------	----------	--------	----------------------	------------------------------	---------------------	----------------------------	---------------	----------------------

Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-steel	13915	8	32	73	20000	M16	16	103	101	50	104	51	12,5
Adjustable leg with foot ø103mm and holes for anchoring, PA+GF-steel	13916	8	32	73	20000	M16	16	103	151	100	154	51	12,5
Adjustable leg with foot ø103mm and holes for anchoring, PA+GF-steel	13917	8	32	73	20000	M16	16	103	201	150	204	51	12,5
Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-steel	13918	8	32	73	20000	M16	16	103	251	200	254	51	12,5
Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-steel	14397	8	32	73	25000	M20	20	103	126	75	129	51	12,5

Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-steel	14398	8	32	73	25000	M20	20	103	151	100	154	51	12,5
---	-------	---	----	----	-------	-----	----	-----	-----	-----	-----	----	------

Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-steel	14399	8	32	73	25000	M20	20	103	176	125	179	51	12,5
---	-------	---	----	----	-------	-----	----	-----	-----	-----	-----	----	------

Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-steel	14400	8	32	73	25000	M20	20	103	201	150	204	51	12,5
---	-------	---	----	----	-------	-----	----	-----	-----	-----	-----	----	------

Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-steel	14401	0	32	73	25000	M20	20	103	226	175	229	51	12,5
---	-------	---	----	----	-------	-----	----	-----	-----	-----	-----	----	------

Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-steel	14402	0	32	73	25000	M20	20	103	251	200	254	51	12,5
---	-------	---	----	----	-------	-----	----	-----	-----	-----	-----	----	------

Adjustable foot with foot \varnothing 103mm and holes for anchoring, PA+GF- steel	14403	0	32	73	25000	M20	20	103	276	225	279	51	12,5
---	-------	---	----	----	-------	-----	----	-----	-----	-----	-----	----	------