

- **Materiál patky:** Termoplast se skleněnými vlákny
- **Materiál šroub:** Pozinkovaná ocel
- **Barva patky:** Černá

Statické zatížení, zmíněné níže v parametrech, je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

K tomuto výrobku si můžete přiojednat [speciální protiskluzovou podložku](#).

Variants

| Product name | Product code | QTY | Thread F | SW key | Foot height G (mm) | Height without washer H (mm) | Screw length B (mm) | Foot diameter D (mm) | Height with washer H1 (mm) | Pitch K (mm) | Hole diameter L (mm) | Static load (N) | Height A (mm) |
|---|--------------|-----|----------|--------|--------------------|------------------------------|---------------------|----------------------|----------------------------|--------------|----------------------|-----------------|---------------|
| Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel | 13936 | 8 | M16 | 13 | 32 | 97 | 50 | 103 | 100 | 73 | 12,5 | 20000 | 47 |
| Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel | 13937 | 8 | M16 | 13 | 32 | 147 | 100 | 103 | 150 | 73 | 12,5 | 20000 | 47 |

| Product name | Product code | QTY | Thread F | SW key | Foot height G (mm) | Height without washer H (mm) | Screw length B (mm) | Foot diameter D (mm) | Height with washer H1 (mm) | Pitch K (mm) | Hole diameter L (mm) | Static load (N) | Height A (mm) |
|---|--------------|-----|----------|--------|--------------------|------------------------------|---------------------|----------------------|----------------------------|--------------|----------------------|-----------------|---------------|
| Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel | 13938 | 8 | M16 | 13 | 32 | 197 | 150 | 103 | 200 | 73 | 12,5 | 20000 | 47 |
| Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel | 13939 | 2 | M16 | 13 | 32 | 247 | 200 | 103 | 250 | 73 | 12,5 | 20000 | 47 |
| Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel | 14248 | 8 | M20 | 20 | 32 | 176 | 125 | 103 | 179 | 73 | 12,5 | 25000 | 51 |
| Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel | 14418 | 8 | M20 | 20 | 32 | 126 | 75 | 103 | 129 | 73 | 12,5 | 25000 | 51 |

| Product name | Product code | QTY | Thread F | SW key | Foot height G (mm) | Height without washer H (mm) | Screw length B (mm) | Foot diameter D (mm) | Height with washer H1 (mm) | Pitch K (mm) | Hole diameter L (mm) | Static load (N) | Height A (mm) |
|---|--------------|-----|----------|--------|--------------------|------------------------------|---------------------|----------------------|----------------------------|--------------|----------------------|-----------------|---------------|
| Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel | 14419 | 8 | M20 | 20 | 32 | 151 | 100 | 103 | 154 | 73 | 12,5 | 25000 | 51 |
| Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel | 14420 | 8 | M20 | 20 | 32 | 201 | 150 | 103 | 204 | 73 | 12,5 | 25000 | 51 |
| Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel | 14421 | 0 | M20 | 20 | 32 | 226 | 175 | 103 | 229 | 73 | 12,5 | 25000 | 51 |
| Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel | 14422 | 0 | M20 | 20 | 32 | 251 | 200 | 103 | 254 | 73 | 12,5 | 25000 | 51 |

| Product name | Product code | QTY | Thread F | SW key | Foot height G (mm) | Height without washer H (mm) | Screw length B (mm) | Foot diameter D (mm) | Height with washer H1 (mm) | Pitch K (mm) | Hole diameter L (mm) | Static load (N) | Height A (mm) |
|---|--------------|-----|----------|--------|--------------------|------------------------------|---------------------|----------------------|----------------------------|--------------|----------------------|-----------------|---------------|
| Adjustable foot with foot ø103mm and holes for anchoring, PA+GF-stainless steel | 14423 | 0 | M20 | 20 | 32 | 276 | 225 | 103 | 279 | 73 | 12,5 | 25000 | 51 |