

- **Materiál patka:** galvanizovaná ocel + vulkanizovaná guma NBR 80 Shore
- **Materiál šroub:** galvanizovaná ocel C40
- **Barva patky:** stříbrná + černá

Zmíněné statické zatížení je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

Selected variant

Product name	Adjustable foot with vulcan. foot ø60 mm and eye, galvanized steel
Product code	14447
Foot height G (mm)	22
Pitch I (mm)	45
Height H (mm)	283
Thread F	M20
Static load (N)	7000
Screw length B (mm)	250
Height A (mm)	32
SW key	20
Foot diameter D (mm)	60

Variants

Product name	Product code	QTY	Foot height G (mm)	Pitch I (mm)	Height H (mm)	Thread F	Static load (N)	Screw length B (mm)	Height A (mm)	SW key	Foot diameter D (mm)
Adjustable foot with vulcan. foot ø60 mm and eye, galvanised steel	14431	11	22	45	82	M10	7000	50	32	14	60

Product name	Product code	QTY	Foot height G (mm)	Pitch I (mm)	Height H (mm)	Thread F	Static load (N)	Screw length B (mm)	Height A (mm)	SW key	Foot diameter D (mm)
Adjustable foot with vulcanized foot ø60 mm and eye, galvanized steel	14432	18	22	45	132	M10	7000	100	32	14	60
Adjustable leg with vulcanized foot ø60 mm and eyelet, galvanized steel	14433	0	22	45	82	M12	7000	50	32	14	60
Adjustable foot with vulcan. foot ø60 mm and eye, galvanized steel	14434	4	22	45	132	M12	7000	100	32	14	60
Adjustable leg with vulcanized foot ø60 mm and eyelet, galvanized steel	14435	2	22	45	182	M12	7000	150	32	14	60
Adjustable foot with vulcan. with foot ø60 mm and eyelet, galvanized steel	14436	0	22	45	82	M14	7000	50	32	14	60
Cylindrical covers, silicone, 315°C	14437	0	22	45	132	M14	7000	100	32	14	60
Adjustable clamping lever with screw and ball, metal	14438	0	22	45	182	M14	7000	150	32	14	60

Product name	Product code	QTY	Foot height G (mm)	Pitch I (mm)	Height H (mm)	Thread F	Static load (N)	Screw length B (mm)	Height A (mm)	SW key	Foot diameter D (mm)
Adjustable foot with vulcan. foot ø60 mm and eye, galvanized steel	14439	5	22	45	107	M16	7000	75	32	16	60
Adjustable foot with vulcanized foot ø60 mm and eye, galvanized steel	14440	19	22	45	132	M16	7000	100	32	16	60
Adjustable foot with vulcan. foot ø60 mm and eye, galvanized steel	14441	6	22	45	182	M16	7000	150	32	16	60
Adjustable foot with vulcan. foot ø60 mm and eye, galvanized steel	14442	2	22	45	232	M16	7000	200	32	16	60
Adjustable foot with vulcan. foot ø60 mm and eye, galvanized steel	14443	5	22	45	108	M20	7000	75	32	20	60
Adjustable foot with vulcan. foot ø60 mm and eye, galvanized steel	14444	0	22	45	133	M20	7000	100	32	20	60

Product name	Product code	QTY	Foot height G (mm)	Pitch I (mm)	Height H (mm)	Thread F	Static load (N)	Screw length B (mm)	Height A (mm)	SW key	Foot diameter D (mm)
Nastavitelná noha s vulkan. patkou ø60 mm a očkem, pozink. ocel'	14445	0	22	45	183	M20	7000	150	32	20	60
Adjustable foot with vulcanized foot with foot ø60 mm and eyelet, galvanized. steel	14446	0	22	45	233	M20	7000	200	32	20	60
Adjustable foot with vulcan. foot ø60 mm and eye, galvanized steel	14447	0	22	45	283	M20	7000	250	32	20	60