

Suitable for hydraulic and lubrication systems, fuel or steam supply at high temperatures.

- **Temperature range:** -70°C / +260°C
- **Tube:** single-layer PTFE
- **Reinforcement:** stainless steel AISI 304 braid
- **Surface:** braided

Price is for 1 meter.

## Selected variant

<b>Product name</b>	PTFE braided hose/Stainless steel
<b>Product code</b>	0
<b>Destruction pressure (bar / psi)</b>	480/7200
<b>Bending radius (mm)</b>	70
<b>Working pressure (bar / psi)</b>	120/1800
<b>Inner diameter D (mm)</b>	13
<b>Outer diameter D (mm)</b>	16,2

## Variants

Product name	Product code	QTY	Destruction pressure (bar / psi)	Bending radius (mm)	Working pressure (bar / psi)	Inner diameter D (mm)	Outer diameter D (mm)
PTFE/Stainless steel braided hose	26407	0	540/8100	55	135/2025	9,5	12,3
PTFE braided hose/stainless steel	26405	0	700/10500	45	175/2625	6,5	9
PTFE braided hose/Stainless steel	26422	0	1000/15000	25	250/3750	3,2	5,8
PTFE/Stainless steel braided hose	26404	0	800/12000	35	200/3000	5	7,6

### A components s.r.o.

Bohunická 493/81  
619 00 Brno

Web: [www.acomponents.cz](http://www.acomponents.cz)  
E-mail: [info@acomponents.cz](mailto:info@acomponents.cz)  
Telefon: 511 188 963

### Maloobchodní prodej

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.

Product name	Product code	QTY	Destruction pressure (bar / psi)	Bending radius (mm)	Working pressure (bar / psi)	Inner diameter D (mm)	Outer diameter D (mm)
PTFE braided hose/Stainless steel	26406	0	600/9000	50	150/2250	8	11
PTFE braided hose/Stainless steel	26408	0	480/7200	70	120/1800	13	16,2
PTFE braided hose/Stainless steel	26409	0	400/6000	130	100/1500	16	19
PTFE/Stainless steel braided hose	26410	0	360/5400	190	90/1350	19	23,1
PTFE/Stainless steel braided hose	26411	0	260/3900	270	65/975	25	29,2