

Vhodná pro hydraulické a mazací systémy, dodávku paliva nebo páry při vysokých teplotách.

- **Tepelný rozsah:** -70°C / +250°C
- **Trubka:** spirálová PTFE
- **Výztuž:** nerezový AISI 304 oplet
- **Povrch:** pletený

**Cena je za 1 metr.**

## Variants

| Product name                               | Product code | QTY | Inner diameter D (mm) | Working pressure (bar / psi) | Outer diameter D (mm) | Bending radius (mm) | Destruction pressure (bar / psi) |
|--------------------------------------------|--------------|-----|-----------------------|------------------------------|-----------------------|---------------------|----------------------------------|
| Braided hose, spiral. PTFE/Stainless steel | 26412        | 0   | 6,4                   | 170/2550                     | 9                     | 18                  | 510/7650                         |
| Braided hose, spiral. PTFE/Stainless steel | 26414        | 0   | 9,5                   | 140/2100                     | 13                    | 22                  | 420/6300                         |
| Braided hose, spiral. PTFE/Stainless Steel | 26415        | 0   | 12,7                  | 103/1545                     | 18                    | 25                  | 309/4635                         |
| Braided hose, spiral. PTFE/Stainless Steel | 26413        | 0   | 7,9                   | 155/2325                     | 12                    | 20                  | 465/6975                         |
| Braided hose, spiral. PTFE/Stainless steel | 26416        | 0   | 15,9                  | 83/1245                      | 21                    | 51                  | 249/3735                         |
| Braided hose, spiral. PTFE/Stainless Steel | 26419        | 0   | 32                    | 35/525                       | 40                    | 125                 | 105/1575                         |

### A components s.r.o.

Bohunická 493/81

619 00 Brno

Web: [www.acomponents.cz](http://www.acomponents.cz)

E-mail: [info@acomponents.cz](mailto:info@acomponents.cz)

Telefon: 511 188 963

### Maloobchodní prodej

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.

| Product name                                  | Product code | QTY | Inner diameter D (mm) | Working pressure (bar / psi) | Outer diameter D (mm) | Bending radius (mm) | Destruction pressure (bar / psi) |
|-----------------------------------------------|--------------|-----|-----------------------|------------------------------|-----------------------|---------------------|----------------------------------|
| Braided hose, spiral.<br>PTFE/Stainless steel | 26418        | 0   | 25,4                  | 46/690                       | 32                    | 89                  | 138/2070                         |
| Braided hose, spiral.<br>PTFE/Stainless Steel | 26420        | 0   | 38                    | 30/450                       | 49                    | 150                 | 90/1350                          |
| Braided hose, spiral.<br>PTFE/Stainless Steel | 26417        | 0   | 19                    | 70/1050                      | 24                    | 64                  | 210/3150                         |
| Braided hose, spiral.<br>PTFE/Stainless Steel | 26421        | 0   | 51                    | 23/345                       | 59                    | 200                 | 69/1035                          |