

- **Materiál patka:** Termoplast se skleněnými vlákny
- **Materiál šroub:** Pozinkovaná ocel
- **Barva patky:** Černá

Statické zatížení, zmíněné níže v parametrech, je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

K tomuto výrobku si můžete přiojednat [speciální protiskluzovou podložku](#).

## Selected variant

| Product name                 | Adjustable foot with foot ø65mm, PA+GF-steel |
|------------------------------|----------------------------------------------|
| Product code                 | 13793                                        |
| Height with washer H1 (mm)   | 111                                          |
| Thread F                     | M12                                          |
| Screw length B (mm)          | 75                                           |
| Height without washer H (mm) | 108                                          |
| Static load (N)              | 11000                                        |
| Height A (mm)                | 33                                           |
| SW key                       | 14                                           |
| Foot diameter D (mm)         | 65                                           |
| Foot height G (mm)           | 23                                           |

## Variants

| Product name                                 | Product code | QTY | Height with washer H1 (mm) | Thread F | Screw length B (mm) | Height without washer H (mm) | Static load (N) | Height A (mm) | SW key | Foot diameter D (mm) | Foot height G (mm) |
|----------------------------------------------|--------------|-----|----------------------------|----------|---------------------|------------------------------|-----------------|---------------|--------|----------------------|--------------------|
| Adjustable foot with foot ø65mm, PA+GF-steel | 13788        | 33  | 86                         | M10      | 50                  | 83                           | 11000           | 33            | 14     | 65                   | 23                 |

### A components s.r.o.

Bohunická 493/81

619 00 Brno

Web: [www.acomponents.cz](http://www.acomponents.cz)

E-mail: [info@acomponents.cz](mailto:info@acomponents.cz)

Telefon: 511 188 963

### Maloobchodní prodej

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.

| Product name                                 | Product code | QTY | Height with washer H1 (mm) | Thread F | Screw length B (mm) | Height without washer H (mm) | Static load (N) | Height A (mm) | SW key | Foot diameter D (mm) | Foot height G (mm) |
|----------------------------------------------|--------------|-----|----------------------------|----------|---------------------|------------------------------|-----------------|---------------|--------|----------------------|--------------------|
| Adjustable foot with foot ø65mm, PA+GF-steel | 13789        | 16  | 111                        | M10      | 75                  | 108                          | 11000           | 33            | 14     | 65                   | 23                 |
| Adjustable foot with foot ø65mm, PA+GF-steel | 13790        | 19  | 136                        | M10      | 100                 | 133                          | 11000           | 33            | 14     | 65                   | 23                 |
| Adjustable foot with foot ø65mm, PA+GF-steel | 13791        | 15  | 161                        | M10      | 125                 | 158                          | 11000           | 33            | 14     | 65                   | 23                 |
| Adjustable foot with foot ø65mm, PA+GF-steel | 13792        | 14  | 86                         | M12      | 50                  | 83                           | 11000           | 33            | 14     | 65                   | 23                 |
| Adjustable foot with foot ø65mm, PA+GF-steel | 13793        | 10  | 111                        | M12      | 75                  | 108                          | 11000           | 33            | 14     | 65                   | 23                 |
| Adjustable foot with foot ø65mm, PA+GF-steel | 13794        | 5   | 136                        | M12      | 100                 | 133                          | 11000           | 33            | 14     | 65                   | 23                 |
| Adjustable foot with foot ø65mm, PA+GF-steel | 13795        | 12  | 161                        | M12      | 125                 | 158                          | 11000           | 33            | 14     | 65                   | 23                 |

| Product name                                 | Product code | QTY | Height with washer H1 (mm) | Thread F | Screw length B (mm) | Height without washer H (mm) | Static load (N) | Height A (mm) | SW key | Foot diameter D (mm) | Foot height G (mm) |
|----------------------------------------------|--------------|-----|----------------------------|----------|---------------------|------------------------------|-----------------|---------------|--------|----------------------|--------------------|
| Adjustable foot with foot ø65mm, PA+GF-steel | 13796        | 10  | 86                         | M14      | 50                  | 83                           | 15000           | 33            | 14     | 65                   | 23                 |
| Adjustable foot with foot ø65mm, PA+GF-steel | 13797        | 10  | 111                        | M14      | 75                  | 108                          | 15000           | 33            | 14     | 65                   | 23                 |
| Adjustable foot with foot ø65mm, PA+GF-steel | 13798        | 10  | 136                        | M14      | 100                 | 133                          | 15000           | 33            | 14     | 65                   | 23                 |
| Adjustable foot with foot ø65mm, PA+GF-steel | 13799        | 13  | 161                        | M14      | 125                 | 158                          | 15000           | 33            | 14     | 65                   | 23                 |
| Adjustable foot with foot ø65mm, PA+GF-steel | 13800        | 14  | 186                        | M14      | 150                 | 183                          | 15000           | 33            | 14     | 65                   | 23                 |
| Adjustable foot with foot ø65mm, PA+GF-steel | 13801        | 0   | 211                        | M14      | 175                 | 208                          | 15000           | 33            | 14     | 65                   | 23                 |