

- **Materiál patka:** Termoplast se skleněnými vlákny
- **Materiál šroub:** Pozinkovaná ocel
- **Barva patky:** Černá

Statické zatížení, zmíněné níže v parametrech, je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

K tomuto výrobku si můžete přiojednat [speciální protiskluzovou podložku](#).

Selected variant

Product name	Adjustable foot with foot ø50mm, PA+GF-stainless steel
Product code	0
Height without washer H (mm)	155
SW key	14
Foot diameter D (mm)	50
Foot height G (mm)	20
Static load (N)	11000
Screw length B (mm)	125
Height A (mm)	30
Height with washer H1 (mm)	158
Thread F	M14

Variants

Product name	Product code	QTY	Height without washer H (mm)	SW key	Foot diameter D (mm)	Foot height G (mm)	Static load (N)	Screw length B (mm)	Height A (mm)	Height with washer H1 (mm)	Thread F
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13822	2	55	14	50	20	11000	25	30	58	M12

Product name	Product code	QTY	Height without washer H (mm)	SW key	Foot diameter D (mm)	Foot height G (mm)	Static load (N)	Screw length B (mm)	Height A (mm)	Height with washer H1 (mm)	Thread F
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13823	10	80	14	50	20	11000	50	30	83	M12
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13824	10	105	14	50	20	11000	75	30	108	M12
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13825	10	130	14	50	20	11000	100	30	166	M12
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13826	6	155	14	50	20	11000	125	30	158	M12
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13827	6	80	14	50	20	11000	50	30	83	M14

Product name	Product code	QTY	Height without washer H (mm)	SW key	Foot diameter D (mm)	Foot height G (mm)	Static load (N)	Screw length B (mm)	Height A (mm)	Height with washer H1 (mm)	Thread F
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13828	10	105	14	50	20	11000	75	30	108	M14
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13829	10	130	14	50	20	11000	100	30	166	M14
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13830	2	155	14	50	20	11000	125	30	158	M14
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13817	10	55	14	50	20	11000	25	30	58	M10
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13818	9	80	14	50	20	11000	50	30	83	M10

Product name	Product code	QTY	Height without washer H (mm)	SW key	Foot diameter D (mm)	Foot height G (mm)	Static load (N)	Screw length B (mm)	Height A (mm)	Height with washer H1 (mm)	Thread F
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13819	10	105	14	50	20	11000	75	30	108	M10
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13820	10	130	14	50	20	11000	100	30	166	M10
Adjustable foot with foot ø50mm, PA+GF-stainless steel	13821	10	155	14	50	20	11000	125	30	158	M10