

- **Materiál patka:** termoplast se skleněnými vlákny
- **Materiál šroub:** nerezová ocel
- **Barva patky:** černá

Statické zatížení, zmíněné níže v parametrech, je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

K tomuto výrobku si můžete přiojednat [speciální protiskluzovou podložku](#).

Selected variant

Product name	Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel
Product code	14411
Foot height G (mm)	27
Height A (mm)	41
Foot diameter D (mm)	83
SW key	17
Height with washer H1 (mm)	119
Thread F	M20
Screw length B (mm)	75
Pitch K (mm)	55
Static load (N)	20000
Hole diameter L (mm)	8,5
Height without washer H (mm)	116

Variants

Product name	Product code	QTY	Foot height G (mm)	Height A (mm)	Foot diameter D (mm)	SW key	Height with washer H1 (mm)	Thread F	Screw length B (mm)	Pitch K (mm)	Static load (N)	Hole diameter L (mm)	Height without washer H (mm)

Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13849	0	27	38	83	14	91	M10	50	55	15000	8,5	88
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-stainless steel	13850	0	27	38	83	14	116	M10	75	55	15000	8,5	113
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13851	0	27	38	83	14	141	M10	100	55	15000	8,5	138
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13852	0	27	38	83	14	166	M10	125	55	15000	8,5	163
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13853	0	27	38	83	14	91	M12	50	55	15000	8,5	88

Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13854	0	27	38	83	14	116	M12	75	55	15000	8,5	113
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13855	0	27	38	83	14	141	M12	100	55	15000	8,5	138
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13856	0	27	38	83	14	166	M12	125	55	15000	8,5	163
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13857	0	27	38	83	14	91	M14	50	55	20000	8,5	88
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13858	0	27	38	83	14	116	M14	75	55	20000	8,5	113

Nastavitelná noha s patkou ø83 mm a otvory pro kotvení, PA+GF-nerez	13859	0	27	38	83	14	141	M14	100	55	20000	8,5	138
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13860	0	27	38	83	14	166	M14	125	55	20000	8,5	163
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13861	0	27	38	83	14	191	M14	150	55	20000	8,5	188
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13862	0	27	38	83	14	216	M14	175	55	20000	8,5	213
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	14412	0	27	41	83	17	144	M20	100	55	20000	8,5	141

Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13929	0	27	41	83	13	94	M16	50	55	20000	8,5	91
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13930	0	27	41	83	13	119	M16	75	55	20000	8,5	116
Adjustable leg with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13931	0	27	41	83	13	144	M16	100	55	20000	8,5	141
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13932	0	27	41	83	13	169	M16	125	55	20000	8,5	166
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13933	0	27	41	83	13	194	M16	150	55	20000	8,5	191

Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13934	0	27	41	83	13	219	M16	175	55	20000	8,5	216
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	13935	0	27	41	83	13	244	M16	200	55	20000	8,5	241
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	14411	0	27	41	83	17	119	M20	75	55	20000	8,5	116
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	14413	0	27	41	83	17	169	M20	125	55	20000	8,5	166
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	14414	0	27	41	83	17	194	M20	150	55	20000	8,5	191

Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	14415	0	27	41	83	17	219	M20	175	55	20000	8,5	216
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	14416	0	27	41	83	17	244	M20	200	55	20000	8,5	241
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-stainless steel	14417	0	27	41	83	17	269	M20	225	55	20000	8,5	266
Nastavitelná noha s pátkou ø83 mm a otvory pro kotvení, PA+GF-nerez	28399	0	18	30	83	10	180	M12	150	55	13000	54	177