

- **Body material:** steel
- **Ball material:** stainless steel
- **Color:** black

Increased load.

Selected variant

Product name	Locking screw M24x48mm with ball spring-loaded on hex increased strength steel
Product code	14885
Ball diameter D1 (mm)	15
Thread D	M24
N1	130
Length L (mm)	48
Weight (g)	98
I3	5,5
Y (mm)	12
N2	270

Variants

Product name	Product code	QTY	Ball diameter D1 (mm)	Thread D	N1	Length L (mm)	Weight (g)	I3	Y (mm)	N2
Locking screw with ball spring, for Allen, steel, increased strength	14876	10	1,5	M3	5	9	0,1	0,5	1,5	7
Spring-loaded ball lock screw, for Allen key, steel, increased strength	14877	4	1,5	M4	12	10	0,2	0,8	2	22
Locking screw with spring-loaded ball, for hexagon, steel, increased strength	14878	1	3	M5	19	14	1,1	0,9	3	30

A components s.r.o.

Bohunická 493/81

619 00 Brno

Web: www.acomponents.cz

E-mail: info@acomponents.cz

Telefon: 511 188 963

Maloobchodní prodej

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.

Product name	Product code	QTY	Ball diameter D1 (mm)	Thread D	N1	Length L (mm)	Weight (g)	I3	Y (mm)	N2
Sprung ball lock screw, for hex, steel, increased strength	14879	1	3,5	M6	28	15	1,2	1	3	40
Spring-loaded locking screw with ball, for Allen key, steel, increased force	14880	4	5	M8	47	16	3	1,5	4	73
Spring-loaded ball lock screw, for hex, steel, increased strength	14881	0	6	M10	66	23	8	2	5	100
Sprung ball lock screw, for Allen, steel, increased strength	14882	11	8	M12	66	26	12	2,5	6	120
Sprung ball lock screw, for Allen, steel, increased strength	14883	0	10	M16	90	33	30	3,5	8	180
Spring-loaded ball lock screw, for hex, steel, increased strength	14884	0	12	M20	115	43	63	4,5	10	240
Locking screw M24x48mm with ball spring-loaded on hex increased strength steel	14885	1	15	M24	130	48	98	5,5	12	270