

- **Materiál patka:** Termoplast se skleněnými vlákny
- **Materiál šroub:** Pozinkovaná ocel
- **Barva patky:** Černá

Statické zatížení, zmíněné níže v parametrech, je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

K tomuto výrobku si můžete přiojednat [speciální protiskluzovou podložku](#).

Selected variant

Product name	Adjustable foot with foot ø65mm, PA+GF-steel
Product code	13794
Height with washer H1 (mm)	136
Thread F	M12
Screw length B (mm)	100
Height without washer H (mm)	133
Static load (N)	11000
Height A (mm)	33
SW key	14
Foot diameter D (mm)	65
Foot height G (mm)	23

Variants

Product name	Product code	QTY	Height with washer H1 (mm)	Thread F	Screw length B (mm)	Height without washer H (mm)	Static load (N)	Height A (mm)	SW key	Foot diameter D (mm)	Foot height G (mm)
Adjustable foot with foot ø65mm, PA+GF-steel	13788	33	86	M10	50	83	11000	33	14	65	23

Product name	Product code	QTY	Height with washer H1 (mm)	Thread F	Screw length B (mm)	Height without washer H (mm)	Static load (N)	Height A (mm)	SW key	Foot diameter D (mm)	Foot height G (mm)
Adjustable foot with foot ø65mm, PA+GF-steel	13789	16	111	M10	75	108	11000	33	14	65	23
Adjustable foot with foot ø65mm, PA+GF-steel	13790	19	136	M10	100	133	11000	33	14	65	23
Adjustable foot with foot ø65mm, PA+GF-steel	13791	15	161	M10	125	158	11000	33	14	65	23
Adjustable foot with foot ø65mm, PA+GF-steel	13792	14	86	M12	50	83	11000	33	14	65	23
Adjustable foot with foot ø65mm, PA+GF-steel	13793	10	111	M12	75	108	11000	33	14	65	23
Adjustable foot with foot ø65mm, PA+GF-steel	13794	5	136	M12	100	133	11000	33	14	65	23
Adjustable foot with foot ø65mm, PA+GF-steel	13795	12	161	M12	125	158	11000	33	14	65	23

Product name	Product code	QTY	Height with washer H1 (mm)	Thread F	Screw length B (mm)	Height without washer H (mm)	Static load (N)	Height A (mm)	SW key	Foot diameter D (mm)	Foot height G (mm)
Adjustable foot with foot ø65mm, PA+GF-steel	13796	10	86	M14	50	83	15000	33	14	65	23
Adjustable foot with foot ø65mm, PA+GF-steel	13797	10	111	M14	75	108	15000	33	14	65	23
Adjustable foot with foot ø65mm, PA+GF-steel	13798	10	136	M14	100	133	15000	33	14	65	23
Adjustable foot with foot ø65mm, PA+GF-steel	13799	13	161	M14	125	158	15000	33	14	65	23
Adjustable foot with foot ø65mm, PA+GF-steel	13800	14	186	M14	150	183	15000	33	14	65	23
Adjustable foot with foot ø65mm, PA+GF-steel	13801	0	211	M14	175	208	15000	33	14	65	23