

- **Materiál patka:** galvanizovaná ocel + vulkanizovaná guma NBR 80 Shore
- **Materiál šroub:** galvanizovaná ocel C40
- **Barva patky:** stříbrná + černá

Zmíněné statické zatížení je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

## Selected variant

| Product name         | Adjustable foot with vulcanized foot ø100 mm and eye, galvanized steel |
|----------------------|------------------------------------------------------------------------|
| Product code         | 14470                                                                  |
| Foot height G (mm)   | 28                                                                     |
| Static load (N)      | 15000                                                                  |
| Height H (mm)        | 137,5                                                                  |
| Screw length B (mm)  | 100                                                                    |
| Height A (mm)        | 37,5                                                                   |
| Pitch I (mm)         | 69                                                                     |
| SW key               | 16                                                                     |
| Foot diameter D (mm) | 100                                                                    |
| Thread F             | M16                                                                    |

## Variants

| Product name                                                        | Product code | QTY | Foot height G (mm) | Static load (N) | Height H (mm) | Screw length B (mm) | Height A (mm) | Pitch I (mm) | SW key | Foot diameter D (mm) | Thread F |
|---------------------------------------------------------------------|--------------|-----|--------------------|-----------------|---------------|---------------------|---------------|--------------|--------|----------------------|----------|
| Adjustable foot with vulcan. foot ø100 mm and eye, galvanized steel | 14479        | 0   | 28                 | 15000           | 188,5         | 150                 | 38,5          | 69           | 24     | 100                  | M24      |

| Product name                                                              | Product code | QTY | Foot height G (mm) | Static load (N) | Height H (mm) | Screw length B (mm) | Height A (mm) | Pitch I (mm) | SW key | Foot diameter D (mm) | Thread F |
|---------------------------------------------------------------------------|--------------|-----|--------------------|-----------------|---------------|---------------------|---------------|--------------|--------|----------------------|----------|
| Adjustable foot with vulcan. foot ø100 mm and eye, galvanized steel       | 14480        | 5   | 28                 | 15000           | 238,5         | 200                 | 38,5          | 69           | 24     | 100                  | M24      |
| Adjustable foot with vulcan. foot ø100 mm and eye, galvanized steel       | 14481        | 0   | 28                 | 15000           | 288,5         | 250                 | 38,5          | 69           | 24     | 100                  | M24      |
| Adjustable leg with vulcanized foot ø100 mm and eye, galvanised steel     | 14482        | 11  | 28                 | 15000           | 139,5         | 100                 | 39,5          | 69           | 30     | 100                  | M30      |
| Adjustable foot with vulcanized foot ø100 mm and eyelet, galvanized steel | 14483        | 0   | 28                 | 15000           | 189,5         | 150                 | 39,5          | 69           | 30     | 100                  | M30      |
| Adjustable leg with vulcanized foot ø100 mm and eyelet, galvanized. steel | 14484        | 0   | 28                 | 15000           | 239,5         | 200                 | 39,5          | 69           | 30     | 100                  | M30      |
| Adjustable foot with vulcanized foot ø100 mm and eye, galvanized steel    | 14485        | 0   | 28                 | 15000           | 289,5         | 250                 | 39,5          | 69           | 30     | 100                  | M30      |

| Product name                                                           | Product code | QTY | Foot height G (mm) | Static load (N) | Height H (mm) | Screw length B (mm) | Height A (mm) | Pitch I (mm) | SW key | Foot diameter D (mm) | Thread F |
|------------------------------------------------------------------------|--------------|-----|--------------------|-----------------|---------------|---------------------|---------------|--------------|--------|----------------------|----------|
| Adjustable foot with vulcan. foot ø100 mm and eye, galvanized steel    | 14469        | 5   | 28                 | 15000           | 112,5         | 75                  | 37,5          | 69           | 16     | 100                  | M16      |
| Adjustable foot with vulcanized foot ø100 mm and eye, galvanized steel | 14470        | 18  | 28                 | 15000           | 137,5         | 100                 | 37,5          | 69           | 16     | 100                  | M16      |
| Adjustable foot with vulcan. foot ø100 mm and eye, galvanized steel    | 14471        | 6   | 28                 | 15000           | 187,5         | 150                 | 37,5          | 69           | 16     | 100                  | M16      |
| Adjustable foot with vulcan. foot ø100 mm and eye, galvanized steel    | 14472        | 2   | 28                 | 15000           | 237,5         | 200                 | 37,5          | 69           | 16     | 100                  | M16      |
| Adjustable leg with vulcanized foot ø100 mm and eye, galvanized. steel | 14473        | 5   | 28                 | 15000           | 113,5         | 75                  | 38,5          | 69           | 20     | 100                  | M20      |
| Adjustable foot with vulcan. foot ø100 mm and eye, galvanized. steel   | 14474        | 0   | 28                 | 15000           | 138,5         | 100                 | 38,5          | 69           | 20     | 100                  | M20      |

| Product name                                                              | Product code | QTY | Foot height G (mm) | Static load (N) | Height H (mm) | Screw length B (mm) | Height A (mm) | Pitch I (mm) | SW key | Foot diameter D (mm) | Thread F |
|---------------------------------------------------------------------------|--------------|-----|--------------------|-----------------|---------------|---------------------|---------------|--------------|--------|----------------------|----------|
| Adjustable foot with vulcan. foot ø100 mm and eye, galvanized steel       | 14475        | 0   | 28                 | 15000           | 188,5         | 150                 | 38,5          | 69           | 20     | 100                  | M20      |
| Adjustable foot with vulcan. with foot ø100 mm and eye, galvanized steel  | 14476        | 0   | 28                 | 15000           | 238,5         | 200                 | 38,5          | 69           | 20     | 100                  | M20      |
| Adjustable foot with vulcanized foot ø100 mm and eyelet, galvanized steel | 14477        | 0   | 28                 | 15000           | 288,5         | 250                 | 38,5          | 69           | 20     | 100                  | M20      |
| Adjustable leg with vulcanized foot ø100 mm and eye, galvanized steel     | 14478        | 10  | 28                 | 15000           | 138,5         | 100                 | 38,5          | 69           | 24     | 100                  | M24      |