

- **Foot material:** thermoplastic with glass fibers
- **Screw material:** stainless steel
- **Foot color:** black

The static load, mentioned below in the parameters, is calculated on the center of the screw. In the case of vibrations or dynamic loads, these values are reduced.

You can additionally order [a special anti-slip pad](#) for this product.

Selected variant

Product name	Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel
Product code	14409
Pitch K (mm)	87
Static load (N)	35000
Foot height G (mm)	37
Height with washer H1 (mm)	260
Screw length B (mm)	200
Height A (mm)	57
Height without washer H (mm)	257
Thread F	M20
SW key	20
Foot diameter D (mm)	123
Hole diameter L (mm)	12,5

Variants

Product name	Product code	QTY	Pitch K (mm)	Static load (N)	Foot height G (mm)	Height with washer H1 (mm)	Screw length B (mm)	Height A (mm)	Height without washer H (mm)	Thread F	SW key	Foot diameter D (mm)	Hole diameter L (mm)
--------------	--------------	-----	--------------	-----------------	--------------------	----------------------------	---------------------	---------------	------------------------------	----------	--------	----------------------	----------------------

A components s.r.o.

Bohunická 493/81

619 00 Brno

Web: www.acomponents.cz

E-mail: info@acomponents.cz

Telefon: 511 188 963

Maloobchodní prodej

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.

Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel	13925	0	87	35000	37	110	50	57	107	M16	20	123	12,5
Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel	13926	0	87	35000	37	160	100	57	157	M16	20	123	12,5
Adjustable leg with foot ø123 mm and holes for anchoring, PA+GF-steel	13927	0	87	35000	37	210	150	57	207	M16	20	123	12,5
Nastavitelná noha s pátkou ø123 mm a otvory pro kotvení, PA+GF-ocel'	13928	0	87	35000	37	260	200	57	257	M16	20	123	12,5
Adjustable foot with with foot ø123 mm and holes for anchoring, PA+GF-steel	14404	0	87	35000	37	135	75	57	132	M20	20	123	12,5
Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel	14405	0	87	35000	37	160	100	57	157	M20	20	123	12,5

Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel	14406	0	87	35000	37	185	125	57	192	M20	20	123	12,5
Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel	14407	0	87	35000	37	210	150	57	207	M20	20	123	12,5
Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel	14408	0	87	35000	37	235	175	57	232	M20	20	123	12,5
Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel	14409	0	87	35000	37	260	200	57	257	M20	20	123	12,5
Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel	14410	0	87	35000	37	285	225	57	282	M20	20	123	12,5