

- **Materiál patky:** termoplast se skleněnými vlákny
- **Materiál šroub:** nerezová ocel
- **Barva patky:** černá

Statické zatížení, zmíněné níže v parametrech, je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

K tomuto výrobku si můžete přibjednat [speciální protiskluzovou podložku](#).

Selected variant

Product name	Adjustable foot with foot ø40mm, PA+GF-stainless steel
Product code	13889
Height A (mm)	27
Screw length B (mm)	100
Height with washer H1 (mm)	130
Foot diameter D (mm)	40
Foot height G (mm)	16,5
Height without washer H (mm)	127
SW key	12
Thread F	M10
Static load (N)	10000

Variants

Product name	Product code	QTY	Height A (mm)	Screw length B (mm)	Height with washer H1 (mm)	Foot diameter D (mm)	Foot height G (mm)	Height without washer H (mm)	SW key	Thread F	Static load (N)
Adjustable foot with foot ø40mm, PA+GF-stainless steel	13889	0	27	100	130	40	16,5	127	12	M10	10000

Product name	Product code	QTY	Height A (mm)	Screw length B (mm)	Height with washer H1 (mm)	Foot diameter D (mm)	Foot height G (mm)	Height without washer H (mm)	SW key	Thread F	Static load (N)
Adjustable foot with foot ø40mm, PA+GF-stainless steel	13890	6	27	125	155	40	16,5	152	12	M10	10000
Adjustable foot with foot ø40mm, PA+GF-stainless steel	13893	4	27	75	105	40	16,5	102	12	M12	10000
Adjustable foot with foot ø40mm, PA+GF-stainless steel	13894	131	27	100	130	40	16,5	127	12	M12	10000
Adjustable foot with foot ø40mm, PA+GF-stainless steel	13895	6	27	125	155	40	16,5	152	12	M12	10000
Adjustable foot with foot ø40mm, PA+GF-stainless steel	13882	0	27	25	55	40	16,5	52	12	M8	10000
Adjustable foot with foot ø40mm, PA+GF-stainless steel	13883	1	27	50	80	40	16,5	77	12	M8	10000
Adjustable foot with foot ø40mm, PA+GF-stainless steel	13884	2	27	75	105	40	16,5	102	12	M8	10000

Product name	Product code	QTY	Height A (mm)	Screw length B (mm)	Height with washer H1 (mm)	Foot diameter D (mm)	Foot height G (mm)	Height without washer H (mm)	SW key	Thread F	Static load (N)
Adjustable foot with foot ø40mm, PA+GF-stainless steel	13885	131	27	100	130	40	16,5	127	12	M8	10000
Adjustable foot with foot ø40mm, PA+GF-stainless steel	13886	5	27	25	55	40	16,5	52	12	M10	10000
Nastavitelná noha s pätkou ø40mm, PA+GF-nerez	13887	11	27	50	80	40	16,5	77	12	M10	10000
Adjustable foot with foot ø40mm, PA+GF-stainless steel	13888	6	27	75	105	40	16,5	102	12	M10	10000
Adjustable foot with foot ø40mm, PA+GF-stainless steel	13891	0	27	25	55	40	16,5	52	12	M12	10000
Adjustable leg with foot ø40mm, PA+GF-stainless steel	13892	0	27	50	80	40	16,5	77	12	M12	10000