

- **Materiál patka:** galvanizovaná ocel + vulkanizovaná guma NBR 80 Shore
- **Materiál šroub:** galvanizovaná ocel C40
- **Barva patky:** stříbrná + černá

Zmíněné statické zatížení je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

Selected variant

Product name	Adjustable leg with vulcanized foot ø100 mm and eye, galvanized steel
Product code	14478
Foot height G (mm)	28
Static load (N)	15000
Height H (mm)	138,5
Screw length B (mm)	100
Height A (mm)	38,5
Pitch I (mm)	69
SW key	24
Foot diameter D (mm)	100
Thread F	M24

Variants

Product name	Product code	QTY	Foot height G (mm)	Static load (N)	Height H (mm)	Screw length B (mm)	Height A (mm)	Pitch I (mm)	SW key	Foot diameter D (mm)	Thread F
Adjustable foot with vulcan. foot ø100 mm and eye, galvanized steel	14479	0	28	15000	188,5	150	38,5	69	24	100	M24

Product name	Product code	QTY	Foot height G (mm)	Static load (N)	Height H (mm)	Screw length B (mm)	Height A (mm)	Pitch I (mm)	SW key	Foot diameter D (mm)	Thread F
Adjustable foot with vulcan. foot ø100 mm and eye, galvanized steel	14480	5	28	15000	238,5	200	38,5	69	24	100	M24
Adjustable foot with vulcan. foot ø100 mm and eye, galvanized steel	14481	0	28	15000	288,5	250	38,5	69	24	100	M24
Adjustable leg with vulcanized foot ø100 mm and eye, galvanised steel	14482	11	28	15000	139,5	100	39,5	69	30	100	M30
Adjustable foot with vulcanized foot ø100 mm and eyelet, galvanized steel	14483	0	28	15000	189,5	150	39,5	69	30	100	M30
Adjustable leg with vulcanized foot ø100 mm and eyelet, galvanized. steel	14484	0	28	15000	239,5	200	39,5	69	30	100	M30
Adjustable foot with vulcanized foot ø100 mm and eye, galvanized steel	14485	0	28	15000	289,5	250	39,5	69	30	100	M30

Product name	Product code	QTY	Foot height G (mm)	Static load (N)	Height H (mm)	Screw length B (mm)	Height A (mm)	Pitch I (mm)	SW key	Foot diameter D (mm)	Thread F
Adjustable foot with vulcan. foot ø100 mm and eye, galvanized steel	14469	5	28	15000	112,5	75	37,5	69	16	100	M16
Adjustable foot with vulcanized foot ø100 mm and eye, galvanized steel	14470	18	28	15000	137,5	100	37,5	69	16	100	M16
Adjustable foot with vulcan. foot ø100 mm and eye, galvanized steel	14471	6	28	15000	187,5	150	37,5	69	16	100	M16
Adjustable foot with vulcan. foot ø100 mm and eye, galvanized steel	14472	2	28	15000	237,5	200	37,5	69	16	100	M16
Adjustable leg with vulcanized foot ø100 mm and eye, galvanized. steel	14473	5	28	15000	113,5	75	38,5	69	20	100	M20
Adjustable foot with vulcan. foot ø100 mm and eye, galvanized. steel	14474	0	28	15000	138,5	100	38,5	69	20	100	M20

Product name	Product code	QTY	Foot height G (mm)	Static load (N)	Height H (mm)	Screw length B (mm)	Height A (mm)	Pitch I (mm)	SW key	Foot diameter D (mm)	Thread F
Adjustable foot with vulcan. foot ø100 mm and eye, galvanized steel	14475	0	28	15000	188,5	150	38,5	69	20	100	M20
Adjustable foot with vulcan. with foot ø100 mm and eye, galvanized steel	14476	0	28	15000	238,5	200	38,5	69	20	100	M20
Adjustable foot with vulcanized foot ø100 mm and eyelet, galvanized steel	14477	0	28	15000	288,5	250	38,5	69	20	100	M20
Adjustable leg with vulcanized foot ø100 mm and eye, galvanized steel	14478	10	28	15000	138,5	100	38,5	69	24	100	M24