

Suitable for hydraulic and lubrication systems, fuel or steam supply at high temperatures.

- **Temperature range:** -70°C / +250°C
- **Tube:** spiral PTFE
- **Reinforcement:** stainless steel AISI 304 braid
- **Surface:** braided

The price is for 1 meter.

## Selected variant

<b>Product name</b>	Braided hose, spiral. PTFE/Stainless Steel
<b>Product code</b>	0
<b>Inner diameter D (mm)</b>	51
<b>Working pressure (bar / psi)</b>	23/345
<b>Outer diameter D (mm)</b>	59
<b>Bending radius (mm)</b>	200
<b>Destruction pressure (bar / psi)</b>	69/1035

## Variants

Product name	Product code	QTY	Inner diameter D (mm)	Working pressure (bar / psi)	Outer diameter D (mm)	Bending radius (mm)	Destruction pressure (bar / psi)
Braided hose, spiral. PTFE/Stainless steel	26412	0	6,4	170/2550	9	18	510/7650
Braided hose, spiral. PTFE/Stainless steel	26414	0	9,5	140/2100	13	22	420/6300
Braided hose, spiral. PTFE/Stainless Steel	26415	0	12,7	103/1545	18	25	309/4635

Product name	Product code	QTY	Inner diameter D (mm)	Working pressure (bar / psi)	Outer diameter D (mm)	Bending radius (mm)	Destruction pressure (bar / psi)
Braided hose, spiral. PTFE/Stainless Steel	26413	0	7,9	155/2325	12	20	465/6975
Braided hose, spiral. PTFE/Stainless steel	26416	0	15,9	83/1245	21	51	249/3735
Braided hose, spiral. PTFE/Stainless Steel	26419	0	32	35/525	40	125	105/1575
Braided hose, spiral. PTFE/Stainless steel	26418	0	25,4	46/690	32	89	138/2070
Braided hose, spiral. PTFE/Stainless Steel	26420	0	38	30/450	49	150	90/1350
Braided hose, spiral. PTFE/Stainless Steel	26417	0	19	70/1050	24	64	210/3150
Braided hose, spiral. PTFE/Stainless Steel	26421	0	51	23/345	59	200	69/1035