

Spiral for protecting hydraulic hoses against mechanical damage with high temperature resistance. Suitable for use in mining environments.

- **Material:** Polyamide (Nylon), spiral extrusion
- **Color:** Black
- **Temperature range of use:** -35 °C/+125 °C
- **Certification:** MSHA IC-334/02, tested according to UL-94 standard
- Meets the conditions of V-2 classification.

The price is for 1 meter.

It is possible that the required quantity will not be in stock. In this case, we will contact you.

Selected variant

Product name	Protective spirals -35°C/125°C, PA, MSHA, black
Product code	0
Outer diameter D (mm)	20
Inner diameter D (mm)	16

Variants

Product name	Product code	QTY	Outer diameter D (mm)	Inner diameter D (mm)
Protective spirals -35°C/125°C, PA, MSHA, black	11918	50	12	8
Protective spirals -35°C/125°C, PA, MSHA, black	11919	115	16	12
Protective spirals -35°C/125°C, PA, MSHA, black	11920	264	20	16
Protective spirals -35°C/125°C, PA, MSHA, black	11921	50	25	20
Protective spirals -35°C/125°C, PA, MSHA, black	11922	182	29	25
Protective spirals -35°C/125°C, PA, MSHA, black	11923	162	32	27
Protective spirals -35°C/125°C, PA, MSHA, black	11924	0	35	30

Product name	Product code	QTY	Outer diameter D (mm)	Inner diameter D (mm)
Protective spirals -35°C/125°C, PA, MSHA, black	25843	135	40	35
Protective spirals -35°C/125°C, PA, MSHA, black	25845	0	63	56
Protective spirals -35°C/125°C, PA, MSHA, black	25844	0	50	44

A components s.r.o.

Bohunická 493/81
619 00 Brno

Web: www.acomponents.cz
E-mail: info@acomponents.cz
Telefon: 511 188 963

Maloobchodní prodej

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.