

- **Foot material:** Thermoplastic with glass fibers
- **Screw material:** Stainless steel
- **Color feet:** Black

The static load mentioned in the parameters is calculated on the center of the screw. In case of vibrations or dynamic loads, these values are reduced.

You can order a special [protišmiková podloska](#) for this product.

## Selected variant

<b>Product name</b>	Adjustable foot with foot $\varnothing$ 123mm and holes for anchoring, PA+GF-stainless steel
<b>Product code</b>	14426
<b>Height without washer H (mm)</b>	192
<b>Pitch K (mm)</b>	87
<b>SW key</b>	20
<b>Height with washer H1 (mm)</b>	185
<b>Foot height G (mm)</b>	37
<b>Screw length B (mm)</b>	125
<b>Thread F</b>	M20
<b>Foot diameter D (mm)</b>	123
<b>Hole diameter L (mm)</b>	12,5
<b>Static load (N)</b>	35000
<b>Height A (mm)</b>	57

## Variants

Product name	Product code	QTY	Height without washer H (mm)	Pitch K (mm)	SW key	Height with washer H1 (mm)	Foot height G (mm)	Screw length B (mm)	Thread F	Foot diameter D (mm)	Hole diameter L (mm)	Static load (N)	Height A (mm)
--------------	--------------	-----	------------------------------	--------------	--------	----------------------------	--------------------	---------------------	----------	----------------------	----------------------	-----------------	---------------

Adjustable foot with foot ø123mm and holes for anchoring, PA+GF-stainless steel	14624	0	233	87	26	236	37	175	M30	123	12,5	35000	58
Adjustable foot with foot ø123mm and holes for anchoring, PA+GF-stainless steel	13940	0	107	87	20	110	37	50	M16	123	12,5	35000	57
Adjustable foot with foot ø123mm and holes for anchoring, PA+GF-stainless steel	13941	0	157	87	20	160	37	100	M16	123	12,5	35000	57
Adjustable foot with foot ø123mm and holes for anchoring, PA+GF-stainless steel	13942	0	207	87	20	210	37	150	M16	123	12,5	35000	57

Adjustable foot with foot o123mm and holes for anchoring, PA+GF-stainless steel	13943	0	257	87	20	260	37	200	M16	123	12,5	35000	57
Adjustable foot with foot o123mm and holes for anchoring, PA+GF-stainless steel	14424	0	132	87	20	135	37	75	M20	123	12,5	35000	57
Adjustable foot with foot o123mm and holes for anchoring, PA+GF-stainless steel	14425	0	157	87	20	160	37	100	M20	123	12,5	35000	57
Adjustable foot with foot o123mm and holes for anchoring, PA+GF-stainless steel	14426	0	192	87	20	185	37	125	M20	123	12,5	35000	57

Adjustable foot with foot o123mm and holes for anchoring, PA+GF-stainless steel	14427	0	207	87	20	210	37	150	M20	123	12,5	35000	57
Adjustable foot with foot o123mm and holes for anchoring, PA+GF-stainless steel	14428	0	232	87	20	235	37	175	M20	123	12,5	35000	57
Adjustable foot with foot o123mm and holes for anchoring, PA+GF-stainless steel	14429	0	257	87	20	260	37	200	M20	123	12,5	35000	57
Adjustable foot with foot o123mm and holes for anchoring, PA+GF-stainless steel	14430	0	282	87	20	285	37	225	M20	123	12,5	35000	57