

Silent blocks are standardly made of NR/SBR rubber with a hardness of 70 ±5 Shore.

Working temperature range from -20°C to 80°C.

These silent blocks are designed for pressure loads (axial load downwards). They are not intended for tensile or shear loads (axial load upwards or radial load).

In case the product is not in stock in sufficient quantities, its delivery time can be up to 120 days.

Selected variant

Product name	Silent block thread, Type 5
Product code	27087
Length L (mm)	40
Thread depth H (mm)	10
Diameter d (mm)	M10
Diameter D (mm)	50

Variants

Product name	Product code	QTY	Length L (mm)	Thread depth H (mm)	Diameter d (mm)	Diameter D (mm)
Metric glands, with nut, PA, gray	27055	1154	15	6	M6	20
Silent block thread, Type 5	27052	0	20	4	M4	15
Silent block thread, Type 5	27058	0	30	6	M6	20
Silent block thread, Type 5	27056	0	20	6	M6	20
Silent block thread, Type 5	27063	0	20	6	M6	25
Silent block thread, Type 5	27065	0	25	6	M6	25
Silent block thread, Type 5	27069	0	20	8	M8	30
Silent block thread, Type 5	27072	0	30	8	M8	30
Silent block thread, Type 5	27080	0	40	8	M8	40
Silent block thread, Type 5	27079	0	30	8	M8	40
Silent block thread, Type 5	27083	0	20	10	M10	50

Product name	Product code	QTY	Length L (mm)	Thread depth H (mm)	Diameter d (mm)	Diameter D (mm)
Silent block thread, Type 5	27085	0	30	10	M10	50
Silent block thread, Type 5	27087	0	40	10	M10	50
Silentblok thread, Type 5	27086	0	35	10	M10	50
Silent block thread, Type 5	27090	0	50	10	M10	50
Silent block thread, Type 5	27091	0	25	12	M12	60
Silent block thread, Type 5	27092	0	30	12	M12	60
Silent block thread, Type 5	27094	0	40	12	M12	60
Silent block thread, Type 5	27097	0	45	12	M12	70
Silent block thread, Type 5	27099	0	30	12	M12	75
Silent block thread, Type 5	27102	0	50	12	M12	75
Silent block thread, Type 5	27107	0	50	16	M16	100
	27105	0	30	16	M16	100
	27106	0	40	16	M16	100
	27108	0	55	16	M16	100
	27109	0	60	16	M16	100
	27110	0	75	16	M16	100
	27048	0	10	4	M4	10
	27111	0	40	16	M16	125
	27112	0	45	16	M20	150
	27113	0	50	16	M20	150
	27114	0	55	16	M20	150
	27115	0	60	16	M20	150
	27050	0	10	4	M4	15
	27051	0	15	4	M4	15
	27049	0	8	4	M4	15
	27054	0	10	6	M6	20
	27057	0	25	6	M6	20

Product name	Product code	QTY	Length L (mm)	Thread depth H (mm)	Diameter d (mm)	Diameter D (mm)
	27053	0	8	6	M6	20
	27061	0	15	6	M6	25
	27060	0	10	6	M6	25
	27062	0	17	6	M6	25
	27064	0	23	6	M6	25
	27059	0	8	6	M6	25
	27066	0	30	6	M6	25
	27067	0	15	8	M8	30
	27068	0	17	8	M8	30
	27070	0	25	8	M8	30
	27071	0	28	8	M8	30
	27073	0	40	8	M8	30
	27074	0	35	8	M8	35
	27075	0	20	8	M8	40
	27076	0	25	8	M8	40
	27077	0	27	8	M8	40
	27078	0	28	8	M8	40
	27082	0	35	10	M8	45
	27081	0	25	8	M8	45
	27084	0	25	10	M10	50
	27089	0	45	10	M10	50
	27088	0	42	10	M10	50
	27093	0	35	12	M12	60
	27095	0	35	12	M12	70
	27096	0	40	12	M12	70
	27098	0	25	12	M12	75
	27100	0	40	12	M12	75

Product name	Product code	QTY	Length L (mm)	Thread depth H (mm)	Diameter d (mm)	Diameter D (mm)
	27101	0	45	12	M12	75
	27103	0	55	12	M12	75
	27104	0	70	12	M12	75

A components s.r.o.

Bohunická 493/81

619 00 Brno

Web: www.acomponents.czE-mail: info@acomponents.cz

Telefon: 511 188 963

Maloobchodní prodej

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.