

- **Material:** polyamide 6.6 with an additive that increases the material's resistance to UV radiation
- **Color:** black
- **Operating temperature:** -40°C to +85°C
- **Material flammability:** complies with UL 94V-2

Packed in packs of 100.

Certified according to UL 62275 type 2.21 and IEC 62275 type 2; including UV.

Variants

| Product name | Product code | QTY | width | Min. tensile strength (kg) | Maximum closing diameter (mm) | Color | Length L (mm) |
|--------------------------------|--------------|-----|-------|----------------------------|-------------------------------|-------|---------------|
| UV-resistant cable ties, black | 30887 | 0 | 4,5 | 22 | 76 | černá | 280 |
| 0 | 31074 | 0 | 3,5 | 15 | 36 | černá | 140 |
| UV-resistant cable ties, black | 31076 | 0 | 4,5 | 22 | 101 | černá | 360 |
| UV-resistant cable ties, black | 31075 | 0 | 4,5 | 22 | 51 | černá | 200 |
| UV-resistant cable ties, black | 31078 | 0 | 7,5 | 46 | 160 | černá | 540 |
| UV-resistant cable ties, black | 31079 | 0 | 7,5 | 68 | 235 | černá | 750 |
| UV-resistant cable ties, black | 31077 | 0 | 7,5 | 46 | 101 | černá | 360 |