

- **Materiál patka:** Termoplast se skleněnými vlákny
- **Materiál šroub:** Pozinkovaná ocel
- **Barva patky:** Černá

Statické zatížení, zmíněné níže v parametrech, je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

K tomuto výrobku si můžete přiojednat [speciální protiskluzovou podložku](#).

Variants

Product name	Product code	QTY	Foot diameter D (mm)	Thread F	Static load (N)	Height with washer H1 (mm)	Screw length B (mm)	SW key	Height without washer H (mm)	Foot height G (mm)	Height A (mm)
Adjustable leg with foot ø65mm, PA+GF-stainless steel	14625	0	65	M20	15000	215	175	17	212	23	37
Adjustable foot with foot ø65mm, PA+GF-stainless steel	13831	9	65	M10	11000	86	50	14	83	23	33
Adjustable foot with foot ø65mm, PA+GF-stainless steel	14626	11	65	M16	15000	115	75	13	112	23	37
Adjustable foot with foot ø65mm, PA+GF-stainless steel	13832	10	65	M10	11000	111	75	14	108	23	33
Adjustable foot with foot ø65mm, PA+GF-stainless steel	13833	37	65	M10	11000	136	100	14	133	23	33

Product name	Product code	QTY	Foot diameter D (mm)	Thread F	Static load (N)	Height with washer H1 (mm)	Screw length B (mm)	SW key	Height without washer H (mm)	Foot height G (mm)	Height A (mm)
Adjustable foot with foot ø65mm, PA+GF-stainless steel	13834	14	65	M10	11000	161	125	14	158	23	33
Adjustable foot with foot ø65mm, PA+GF-stainless steel	13835	2	65	M12	11000	86	50	14	83	23	33
Adjustable foot with foot ø65mm, PA+GF-stainless steel	13836	10	65	M12	11000	111	75	14	108	23	33
Adjustable foot with foot ø65mm, PA+GF-stainless steel	13837	37	65	M12	11000	136	100	14	133	23	33
Adjustable leg with foot ø65mm, PA+GF-stainless steel	13838	6	65	M12	11000	161	125	14	158	23	33
Adjustable foot with foot ø65mm, PA+GF-stainless steel	13839	6	65	M14	15000	86	50	14	83	23	33
Adjustable foot with foot ø65mm, PA+GF-stainless steel	13840	11	65	M14	15000	111	75	14	108	23	33
Nastavitelná noha s pätkou ø65mm, PA+GF-nerez	13841	17	65	M14	15000	136	100	14	133	23	33

Product name	Product code	QTY	Foot diameter D (mm)	Thread F	Static load (N)	Height with washer H1 (mm)	Screw length B (mm)	SW key	Height without washer H (mm)	Foot height G (mm)	Height A (mm)
Adjustable foot with foot ø65mm, PA+GF-stainless steel	13842	2	65	M14	15000	161	125	14	158	23	33
Adjustable foot with foot ø65mm, PA+GF-stainless steel	13843	12	65	M14	15000	186	150	14	183	23	33
Adjustable foot with foot ø65mm, PA+GF-stainless steel	13844	0	65	M14	15000	211	175	14	208	23	33