

- **Foot material:** Thermoplastic with glass fibers
- **Material screw: Galvanized steel. Foot color: Black. Static load, mentioned below in the parameters, is calculated on the center of the screw. In the case of vibrations or dynamic loads, these values are reduced. You can order a special anti-slip pad for this product. The protective spiral is approved for the MSHA IC-344 standard and is therefore suitable for mining equipment. Flammability is tested in accordance with the UL-94 standard.**
 - **Material:** HD Polyethylene
 - **Color:** dark gray

Price is for 1 meter.

Selected variant

Product name	Adjustable foot with foot ø40mm, PA+GF-steel
Product code	13881
Thread F	M12
Height A (mm)	27
Height with washer H1 (mm)	155
Foot diameter D (mm)	40
SW key	12
Screw length B (mm)	125
Static load (N)	10000
Foot height G (mm)	16,5
Height without washer H (mm)	152

Variants

Product name	Product code	QTY	Thread F	Height A (mm)	Height with washer H1 (mm)	Foot diameter D (mm)	SW key	Screw length B (mm)	Static load (N)	Foot height G (mm)	Height without washer H (mm)
Adjustable foot with foot ø40mm, PA+GF-steel	13863	0	M8	27	55	40	12	25	10000	16,5	52

Product name	Product code	QTY	Thread F	Height A (mm)	Height with washer H1 (mm)	Foot diameter D (mm)	SW key	Screw length B (mm)	Static load (N)	Foot height G (mm)	Height without washer H (mm)
Adjustable foot with foot ø40mm, PA+GF-steel	13864	0	M8	27	80	40	12	50	10000	16,5	77
Nastavitelná noha s pätkou ø40mm, PA+GF-ocel'	13865	0	M8	27	105	40	12	75	10000	16,5	102
Adjustable foot with foot ø40mm, PA+GF-steel	13866	0	M8	27	130	40	12	100	10000	16,5	127
Adjustable foot with foot ø40mm, PA+GF-steel	13867	0	M10	27	55	40	12	25	10000	16,5	52
Adjustable foot with foot ø40mm, PA+GF-steel	13868	7	M10	27	80	40	12	50	10000	16,5	77
Adjustable foot with foot ø40mm, PA+GF-steel	13869	35	M10	27	105	40	12	75	10000	16,5	102
Adjustable foot with foot ø40mm, PA+GF-steel	13875	1	M10	27	130	40	12	100	10000	16,5	127
Adjustable foot with foot ø40mm, PA+GF-steel	13876	4	M10	27	155	40	12	125	10000	16,5	152
Adjustable foot with foot ø40 mm, PA+GF-steel	13877	0	M12	27	55	40	12	25	10000	16,5	52

Product name	Product code	QTY	Thread F	Height A (mm)	Height with washer H1 (mm)	Foot diameter D (mm)	SW key	Screw length B (mm)	Static load (N)	Foot height G (mm)	Height without washer H (mm)
Adjustable foot with foot ø40mm, PA+GF-steel	13878	1	M12	27	80	40	12	50	10000	16,5	77
Adjustable foot with foot ø40mm, PA+GF-steel	13879	0	M12	27	105	40	12	75	10000	16,5	102
Adjustable foot with foot ø40mm, PA+GF-steel	13880	1	M12	27	130	40	12	100	10000	16,5	127
Adjustable foot with foot ø40mm, PA+GF-steel	13881	0	M12	27	155	40	12	125	10000	16,5	152