

Plastové spojky mohou velmi výrazně nahradit svařované spoje. Zvláště u eloxovaných profilů jsou nepostradatelné.

Ocelové jádro v plastové spojce velmi výrazně spoj profilů zpevní. Tyto spojky bývají používány při stavbě konstrukcí regálů, stojanů atd.

Spojky s ocelovým jádrem a bez jádra se mohou kombinovat, např. v regálové sestavě - horní police, kde není již taková zátěž, nemusí být zapotřebí spojek s kovovým jádrem, ale mohou se použít levnější plastové spojky bez jádra.

Spojky s ocelovým jádrem bývají velmi často používány při stavbě akvarijních stěn pro svoji variabilitnost a pevnost.

Selected variant

Product name	Square jack coupling, "L", black
Product code	27393
Height H (mm)	36
Side A (mm)	20
Wall thickness T (mm)	1,5
Steel reinforcement	+

Variants

Product name	Product code	QTY	Height H (mm)	Side A (mm)	Wall thickness T (mm)	Steel reinforcement
Square jack coupling, "L", black	27390	0	36	20	1,5	-
Square jack coupling, "L", black	27393	12	36	20	1,5	+
Square yak coupling, "L", black	27391	14	52	25	1,5	-
Square yak coupling, "L", black	27392	0	47	30	2	-
Square jack coupling, "L", black	27395	0	47	30	2	+
Square yoke coupling, "L", black	27394	12	52	25	1,5	+