

- **Materiál patka:** galvanizovaná ocel + vulkanizovaná guma NBR 80 Shore
- **Materiál šroub:** galvanizovaná ocel C40
- **Barva patky:** stříbrná + černá

Zmíněné statické zatížení je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

## Selected variant

| Product name         | Adjustable foot with vulcan. foot ø80 mm, galvanized steel |
|----------------------|------------------------------------------------------------|
| Product code         | 14346                                                      |
| Height H (mm)        | 136                                                        |
| Foot height G (mm)   | 25                                                         |
| SW key               | 20                                                         |
| Foot diameter D (mm) | 80                                                         |
| Static load (N)      | 10000                                                      |
| Thread F             | M20                                                        |
| Height A (mm)        | 35                                                         |
| Screw length B (mm)  | 100                                                        |

## Variants

| Product name                                                  | Product code | QTY | Height H (mm) | Foot height G (mm) | SW key | Foot diameter D (mm) | Static load (N) | Thread F | Height A (mm) | Screw length B (mm) |
|---------------------------------------------------------------|--------------|-----|---------------|--------------------|--------|----------------------|-----------------|----------|---------------|---------------------|
| Adjustable foot with vulcan. foot ø80 mm, galvanized steel    | 14333        | 1   | 85            | 25                 | 14     | 80                   | 10000           | M10      | 35            | 50                  |
| Adjustable leg with vulcanized foot ø80 mm, galvanized. steel | 14334        | 1   | 135           | 25                 | 14     | 80                   | 10000           | M10      | 35            | 100                 |

| Product name                                                    | Product code | QTY | Height H (mm) | Foot height G (mm) | SW key | Foot diameter D (mm) | Static load (N) | Thread F | Height A (mm) | Screw length B (mm) |
|-----------------------------------------------------------------|--------------|-----|---------------|--------------------|--------|----------------------|-----------------|----------|---------------|---------------------|
| Adjustable foot with vulcan. foot ø80 mm, galvanized steel      | 14335        | 0   | 85            | 25                 | 14     | 80                   | 10000           | M12      | 35            | 50                  |
| Adjustable foot with vulcanized foot ø80mm, galvanized steel    | 14336        | 1   | 135           | 25                 | 14     | 80                   | 10000           | M12      | 35            | 100                 |
| Adjustable leg with vulcanized foot ø80 mm, galvanized steel    | 14337        | 1   | 185           | 25                 | 14     | 80                   | 10000           | M12      | 35            | 150                 |
| Adjustable foot with vulcanized foot ø80 mm, galvanized steel   | 14338        | 0   | 85            | 25                 | 14     | 80                   | 10000           | M14      | 35            | 50                  |
| Adjustable foot with vulcan. foot ø80 mm, galvanized steel      | 14339        | 0   | 135           | 25                 | 14     | 80                   | 10000           | M14      | 35            | 100                 |
| Adjustable foot with vulcan. foot ø80 mm, galvanized steel      | 14340        | 0   | 185           | 25                 | 14     | 80                   | 10000           | M14      | 35            | 150                 |
| Adjustable leg with vulcanized foot ø80 mm, galvanized. steel   | 14341        | 1   | 110           | 25                 | 14     | 80                   | 10000           | M16      | 35            | 75                  |
| Adjustable leg with vulcan. with foot ø80 mm, galvanized. steel | 14342        | 1   | 135           | 25                 | 16     | 80                   | 10000           | M16      | 35            | 100                 |
| Adjustable foot with vulcan. foot ø80 mm, galvanized steel      | 14343        | 1   | 185           | 25                 | 16     | 80                   | 10000           | M16      | 35            | 150                 |

| Product name                                                  | Product code | QTY | Height H (mm) | Foot height G (mm) | SW key | Foot diameter D (mm) | Static load (N) | Thread F | Height A (mm) | Screw length B (mm) |
|---------------------------------------------------------------|--------------|-----|---------------|--------------------|--------|----------------------|-----------------|----------|---------------|---------------------|
| Adjustable foot with vulcan. foot ø80 mm, galvanized steel    | 14344        | 1   | 235           | 25                 | 16     | 80                   | 10000           | M16      | 35            | 200                 |
| Adjustable foot with vulcanized foot ø80 mm, galvanized steel | 14345        | 1   | 111           | 25                 | 20     | 80                   | 10000           | M20      | 35            | 75                  |
| Adjustable foot with vulcan. foot ø80 mm, galvanized steel    | 14346        | 0   | 136           | 25                 | 20     | 80                   | 10000           | M20      | 35            | 100                 |
| Adjustable foot with vulcanized foot ø80 mm, galvanized steel | 14347        | 0   | 186           | 25                 | 20     | 80                   | 10000           | M20      | 35            | 150                 |
| Adjustable foot with vulcanized foot ø80 mm, galvanized steel | 14348        | 0   | 236           | 25                 | 20     | 80                   | 10000           | M20      | 35            | 200                 |
| Adjustable leg with vulcan. foot ø80 mm, galvanized steel     | 14349        | 0   | 286           | 25                 | 20     | 80                   | 10000           | M20      | 35            | 250                 |
| Adjustable foot with vulcan. foot ø80 mm, galvanized steel    | 14350        | 0   | 111           | 25                 | 24     | 80                   | 10000           | M24      | 35            | 75                  |
| Adjustable leg with vulcanized foot ø80 mm, galvanized steel  | 14351        | 1   | 136           | 25                 | 24     | 80                   | 10000           | M24      | 35            | 100                 |
| Adjustable foot with vulcan. foot ø80 mm, galvanized steel    | 14352        | 0   | 186           | 25                 | 24     | 80                   | 10000           | M24      | 35            | 150                 |

| Product name                                                  | Product code | QTY | Height H (mm) | Foot height G (mm) | SW key | Foot diameter D (mm) | Static load (N) | Thread F | Height A (mm) | Screw length B (mm) |
|---------------------------------------------------------------|--------------|-----|---------------|--------------------|--------|----------------------|-----------------|----------|---------------|---------------------|
| Adjustable foot with vulcanized foot ø80 mm, galvanized steel | 14353        | 1   | 236           | 25                 | 24     | 80                   | 10000           | M24      | 35            | 200                 |