

- **Materiál patka:** galvanizovaná ocel + vulkanizovaná guma NBR 80 Shore
- **Materiál šroub:** galvanizovaná ocel C40
- **Barva patky:** stříbrná + černá

Zmíněné statické zatížení je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

Selected variant

Product name	Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel
Product code	14466
SW key	24
Height A (mm)	36
Foot height G (mm)	25
Pitch I (mm)	54
Foot diameter D (mm)	80
Static load (N)	10000
Screw length B (mm)	100
Height H (mm)	136
Thread F	M24

Variants

Product name	Product code	QTY	SW key	Height A (mm)	Foot height G (mm)	Pitch I (mm)	Foot diameter D (mm)	Static load (N)	Screw length B (mm)	Height H (mm)	Thread F
Adjustable leg with vulcanized foot ø80 mm and eyelet, galvanized steel	14449	11	14	35	25	54	80	10000	50	85	M10

Product name	Product code	QTY	SW key	Height A (mm)	Foot height G (mm)	Pitch I (mm)	Foot diameter D (mm)	Static load (N)	Screw length B (mm)	Height H (mm)	Thread F
Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel	14450	13	14	35	25	54	80	10000	100	135	M10
Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel	14451	0	14	35	25	54	80	10000	50	85	M12
Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel	14452	4	14	35	25	54	80	10000	100	135	M12
Pipe covers Type 1, LDPE, natural, yellow, black, red, white	14453	2	14	35	25	54	80	10000	150	185	M12
Adjustable foot with vulcan. with foot ø80 mm and eyelet, galvanized. steel	14454	0	14	35	25	54	80	10000	50	85	M14
Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel	14455	0	14	35	25	54	80	10000	100	135	M14

Product name	Product code	QTY	SW key	Height A (mm)	Foot height G (mm)	Pitch I (mm)	Foot diameter D (mm)	Static load (N)	Screw length B (mm)	Height H (mm)	Thread F
Adjustable foot with vulcan. foot ø80 mm and eyelet, galvanised steel	14456	0	14	35	25	54	80	10000	150	185	M14
Adjustable foot with vulcanized foot ø80 mm and eye, galvanized steel	14457	5	14	35	25	54	80	10000	50	85	M16
Adjustable foot with vulcan. foot ø80 mm and eye, galvanised steel	14458	13	14	35	25	54	80	10000	100	135	M16
Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel	14459	6	14	35	25	54	80	10000	150	185	M16
Adjustable foot with vulcan. with foot ø80 mm and eye, galvanized steel	14460	2	14	35	25	54	80	10000	200	235	M16
Adjustable foot with vulcanized foot ø80 mm and eyelet, galvanized steel	14461	5	20	36	25	54	80	10000	75	111	M20

Product name	Product code	QTY	SW key	Height A (mm)	Foot height G (mm)	Pitch I (mm)	Foot diameter D (mm)	Static load (N)	Screw length B (mm)	Height H (mm)	Thread F
Adjustable foot with vulcanized foot ø80 mm and eye, galvanized steel	14462	0	20	36	25	54	80	10000	100	136	M20
Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel	14463	0	20	36	25	54	80	10000	150	186	M20
Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel	14464	0	20	36	25	54	80	10000	200	236	M20
Adjustable foot with vulcanized foot ø80 mm and eye, galvanized steel	14465	0	24	36	25	54	80	10000	75	111	M24
Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel	14466	10	24	36	25	54	80	10000	100	136	M24
Adjustable foot with vulcanized foot ø80 mm and eye, galvanized steel	14467	0	24	36	25	54	80	10000	150	186	M24

Product name	Product code	QTY	SW key	Height A (mm)	Foot height G (mm)	Pitch I (mm)	Foot diameter D (mm)	Static load (N)	Screw length B (mm)	Height H (mm)	Thread F
Adjustable leg with vulcanized foot ø80 mm and eye, galvanized. steel	14468	5	24	36	25	54	80	10000	200	236	M24