

USIT ring with centering lip USS is a top-notch sealing element designed for maximum reliability and durability. This special ring combines the advantages of a traditional USIT ring with the addition of a vulcanized centering lip, which ensures precise positioning and minimizes the risk of leakage.

When tightening the fitting (connection), the sealing lip rests on the opposing surfaces, which are thus sealed by it. Made of high-quality materials, it is resistant to high pressures and temperatures, which makes it ideal for demanding industrial applications. Thanks to its design, it is easy to install and provides long-term wear protection.

- **Material:** steel/NBR

## Selected variant

|                        |                 |
|------------------------|-----------------|
| <b>Product name</b>    | USIT rings, USS |
| <b>Product code</b>    | 0               |
| <b>Material</b>        | ocel / NBR      |
| <b>Thread</b>          | M14             |
| <b>t.</b>              | 1,5             |
| <b>d.</b>              | 14,7            |
| <b>Diameter D (mm)</b> | 22              |

## Variants

| Product name    | Product code | QTY  | Material   | Thread | t.   | d.    | Diameter D (mm) |
|-----------------|--------------|------|------------|--------|------|-------|-----------------|
| USIT rings, USS | 30551        | 7869 | ocel / NBR | 1/4"   | 2,03 | 13,74 | 20,57           |
| USIT rings, USS | 30562        | 1200 | ocel / NBR | M8     | 1    | 8,7   | 13              |
| USIT rings, USS | 30564        | 1350 | ocel / NBR | M24    | 2    | 24,7  | 32              |
| USIT rings, USS | 30563        | 1194 | ocel / NBR | M20    | 1,5  | 20,7  | 28              |
| USIT rings, USS | 30568        | 613  | ocel / NBR | 2"     | 3,2  | 60,58 | 73,03           |
| USIT rings, USS | 30554        | 2070 | ocel / NBR | 1"     | 2,5  | 33,89 | 42,8            |
| USIT rings, USS | 30555        | 1755 | ocel / NBR | M16    | 1,5  | 16,7  | 24              |
| USIT rings, USS | 30552        | 6229 | ocel / NBR | 3/4"   | 2,5  | 27,05 | 34,93           |
| USIT rings, USS | 30561        | 895  | ocel / NBR | 1 1/4" | 2,5  | 42,93 | 52,38           |
| USIT rings, USS | 30569        | 578  | ocel / NBR | 5/8"   | 2,5  | 23,49 | 31,75           |
| USIT rings, USS | 30549        | 4400 | ocel / NBR | 3/8"   | 2,03 | 17,28 | 23,8            |

| Product name    | Product code | QTY  | Material   | Thread | t.   | d.    | Diameter D (mm) |
|-----------------|--------------|------|------------|--------|------|-------|-----------------|
| USIT rings, USS | 30550        | 4130 | ocel / NBR | 1/2"   | 2,5  | 21,54 | 28,58           |
| USIT rings, USS | 30557        | 1950 | ocel / NBR | M22    | 2    | 22,7  | 30              |
| USIT rings, USS | 30558        | 1020 | ocel / NBR | M18    | 1,5  | 18,7  | 26              |
| USIT rings, USS | 30565        | 1059 | ocel / NBR | M26    | 2    | 26,7  | 35              |
| USIT rings, USS | 30567        | 585  | ocel / NBR | 1 1/2" | 2,5  | 48,44 | 58,6            |
| USIT rings, USS | 30553        | 3335 | ocel / NBR | 1/8"   | 2,03 | 10,37 | 15,88           |
| USIT rings, USS | 30556        | 4330 | ocel / NBR | M14    | 1,5  | 14,7  | 22              |
| USIT rings, USS | 30560        | 1250 | ocel / NBR | M10    | 2,0  | 10,35 | 15,88           |
| USIT rings, USS | 30559        | 1282 | ocel / NBR | M12    | 1,5  | 12,7  | 18              |
| USIT rings, USS | 30570        | 409  | ocel / NBR | M6     | 1    | 6,7   | 10              |
| USIT rings, USS | 30566        | 593  | ocel / NBR | M30    | 2    | 31    | 39              |