

- **Wheel material:** rubber

Steel disc, solid, without brake.

Selected variant

Product name	Load-bearing jack plug with square profile, thermoplastic
Product code	14158
Length Q1 (mm)	47,5
Height H (mm)	10
Static load (N)	9500
Length Q (mm)	50
Thread F	M14
Height H1 (mm)	55

Variants

Product name	Product code	QTY	Length Q1 (mm)	Height H (mm)	Static load (N)	Length Q (mm)	Thread F	Height H1 (mm)
Loading plug with square profile, thermoplastic	14139	13	27,5	6	5500	30	M10	33
Loading caster plug with square profile, thermoplastic	14140	10	27,5	6	5500	30	M12	33
Load-bearing jack plug with square profile, thermoplastic	14141	0	27,5	6	5500	30	M14	33
Square-profile load-bearing plug, thermoplastic	14142	0	27,5	6	5500	30	M16	33
Load-bearing plug with square profile, thermoplastic	14143	14	32,5	8	7000	35	M10	43

Product name	Product code	QTY	Length Q1 (mm)	Height H (mm)	Static load (N)	Length Q (mm)	Thread F	Height H1 (mm)
Square profile load-bearing jack plug, thermoplastic	14144	6	32,5	8	7000	35	M12	43
Load-bearing jack plug with square profile, thermoplastic	14145	0	32,5	8	7000	35	M14	43
Loading jack plug with square profile, thermoplastic	14146	0	32,5	8	7000	35	M16	43
Load-bearing shim plug with square profile, thermoplastic	14147	0	37,5	8	8000	40	M10	43
Load-bearing jack plug with square profile, thermoplastic	14148	20	37,5	8	8000	40	M12	43
Square profile load-bearing plug, thermoplastic	14149	0	37,5	8	8000	40	M14	43
Loading yak plug with square profile, thermoplastic	14150	0	37,5	8	8000	40	M16	43
Square jack plug, load, thermoplastic	14151	0	37,5	8	8000	40	M20	43
Load-bearing jack plug with square profile, thermoplastic	14152	10	36,5	8	8000	40	M10	43
Square profile load-bearing plug, thermoplastic	14153	7	36,5	8	8000	40	M12	43
Loading jack plug with square profile, thermoplastic	14154	0	36,5	8	8000	40	M14	43
Loading jack plug with square profile, thermoplastic	14155	12	36,5	8	8000	40	M16	43
Square profile load-bearing jack plug, thermoplastic	14156	3	36,5	8	8000	40	M20	43

Product name	Product code	QTY	Length Q1 (mm)	Height H (mm)	Static load (N)	Length Q (mm)	Thread F	Height H1 (mm)
Load-bearing jack plug with square profile, thermoplastic	14157	0	47,5	10	9500	50	M12	55
Load-bearing jack plug with square profile, thermoplastic	14158	0	47,5	10	9500	50	M14	55
Zátka jaklu záťažová se štvorcovým profilom, termoplast	14159	0	47,5	10	9500	50	M16	55
Loading jack plug with square profile, thermoplastic	14160	0	47,5	10	9500	50	M20	55
Loading jack plug with square profile, thermoplastic	14161	14	45,5	10	9500	50	M12	55
Zátka jaklu záťažová se štvorcovým profilom, termoplast	14162	0	45,5	10	9500	50	M14	55
Loading plug with square profile, thermoplastic	14163	12	45,5	10	9500	50	M16	55
Load-bearing jack plug with square profile, thermoplastic	14164	13	45,5	10	9500	50	M20	55