

- **Foot material:** Thermoplastic with glass fibers
- **Screw material:** Galvanized steel
- **Foot color:** Black

The static load, mentioned below in the parameters, is calculated on the center of the screw. These values are reduced in the event of vibrations or dynamic loads.

You can order a [special anti-slip pad](#) for this product.

Selected variant

Product name	Adjustable foot with foot ø65mm, PA+GF-steel
Product code	13796
Height with washer H1 (mm)	86
Thread F	M14
Screw length B (mm)	50
Height without washer H (mm)	83
Static load (N)	15000
Height A (mm)	33
SW key	14
Foot diameter D (mm)	65
Foot height G (mm)	23

Variants

Product name	Product code	QTY	Height with washer H1 (mm)	Thread F	Screw length B (mm)	Height without washer H (mm)	Static load (N)	Height A (mm)	SW key	Foot diameter D (mm)	Foot height G (mm)
Adjustable foot with foot ø65mm, PA+GF-steel	13788	33	86	M10	50	83	11000	33	14	65	23

Product name	Product code	QTY	Height with washer H1 (mm)	Thread F	Screw length B (mm)	Height without washer H (mm)	Static load (N)	Height A (mm)	SW key	Foot diameter D (mm)	Foot height G (mm)
Adjustable foot with foot o65mm, PA+GF-steel	13789	16	111	M10	75	108	11000	33	14	65	23
Adjustable foot with foot o65mm, PA+GF-steel	13790	19	136	M10	100	133	11000	33	14	65	23
Adjustable foot with foot o65mm, PA+GF-steel	13791	15	161	M10	125	158	11000	33	14	65	23
Adjustable foot with foot o65mm, PA+GF-steel	13792	14	86	M12	50	83	11000	33	14	65	23
Adjustable foot with foot o65mm, PA+GF-steel	13793	10	111	M12	75	108	11000	33	14	65	23
Adjustable foot with foot o65mm, PA+GF-steel	13794	5	136	M12	100	133	11000	33	14	65	23
Adjustable foot with foot o65mm, PA+GF-steel	13795	12	161	M12	125	158	11000	33	14	65	23

Product name	Product code	QTY	Height with washer H1 (mm)	Thread F	Screw length B (mm)	Height without washer H (mm)	Static load (N)	Height A (mm)	SW key	Foot diameter D (mm)	Foot height G (mm)
Adjustable foot with foot o65mm, PA+GF-steel	13796	10	86	M14	50	83	15000	33	14	65	23
Adjustable foot with foot o65mm, PA+GF-steel	13797	10	111	M14	75	108	15000	33	14	65	23
Adjustable foot with foot o65mm, PA+GF-steel	13798	10	136	M14	100	133	15000	33	14	65	23
Adjustable foot with foot o65mm, PA+GF-steel	13799	13	161	M14	125	158	15000	33	14	65	23
Adjustable foot with foot o65mm, PA+GF-steel	13800	14	186	M14	150	183	15000	33	14	65	23
Adjustable foot with foot o65mm, PA+GF-steel	13801	0	211	M14	175	208	15000	33	14	65	23