

- **Foot material:** Thermoplastic with glass fibers
- **Screw material:** Galvanized steel
- **Foot color:** Black

The static load, mentioned below in the parameters, is calculated at the center of the screw. These values are reduced in the event of vibrations or dynamic loads.

You can order a [special anti-slip pad](#) for this product.

## Selected variant

<b>Product name</b>	Adjustable foot with foot $\varnothing$ 103mm and holes for anchoring, PA+GF-stainless steel
<b>Product code</b>	14248
<b>Thread F</b>	M20
<b>SW key</b>	20
<b>Foot height G (mm)</b>	32
<b>Height without washer H (mm)</b>	176
<b>Screw length B (mm)</b>	125
<b>Foot diameter D (mm)</b>	103
<b>Height with washer H1 (mm)</b>	179
<b>Pitch K (mm)</b>	73
<b>Hole diameter L (mm)</b>	12,5
<b>Static load (N)</b>	25000
<b>Height A (mm)</b>	51

## Variants

Product name	Product code	QTY	Thread F	SW key	Foot height G (mm)	Height without washer H (mm)	Screw length B (mm)	Foot diameter D (mm)	Height with washer H1 (mm)	Pitch K (mm)	Hole diameter L (mm)	Static load (N)	Height A (mm)
--------------	--------------	-----	----------	--------	--------------------	------------------------------	---------------------	----------------------	----------------------------	--------------	----------------------	-----------------	---------------

Adjustable foot with foot o103mm and holes for anchoring, PA+GF-stainless steel	13936	8	M16	13	32	97	50	103	100	73	12,5	20000	47
Adjustable foot with foot o103mm and holes for anchoring, PA+GF-stainless steel	13937	8	M16	13	32	147	100	103	150	73	12,5	20000	47
Adjustable foot with foot o103mm and holes for anchoring, PA+GF-stainless steel	13938	8	M16	13	32	197	150	103	200	73	12,5	20000	47
Adjustable foot with foot o103mm and holes for anchoring, PA+GF-stainless steel	13939	2	M16	13	32	247	200	103	250	73	12,5	20000	47

Adjustable foot with foot o103mm and holes for anchoring, PA+GF-stainless steel	14248	8	M20	20	32	176	125	103	179	73	12,5	25000	51
Adjustable foot with foot o103mm and holes for anchoring, PA+GF-stainless steel	14418	8	M20	20	32	126	75	103	129	73	12,5	25000	51
Adjustable foot with foot o103mm and holes for anchoring, PA+GF-stainless steel	14419	8	M20	20	32	151	100	103	154	73	12,5	25000	51
Adjustable foot with foot o103mm and holes for anchoring, PA+GF-stainless steel	14420	8	M20	20	32	201	150	103	204	73	12,5	25000	51

Adjustable foot with foot o103mm and holes for anchoring, PA+GF-stainless steel	14421	0	M20	20	32	226	175	103	229	73	12,5	25000	51
Adjustable foot with foot o103mm and holes for anchoring, PA+GF-stainless steel	14422	0	M20	20	32	251	200	103	254	73	12,5	25000	51
Adjustable foot with foot o103mm and holes for anchoring, PA+GF-stainless steel	14423	0	M20	20	32	276	225	103	279	73	12,5	25000	51