

- **Materiál patky:** Termoplast se skleněnými vlákny
- **Materiál šroub:** Nerezová ocel
- **Barva patky:** Černá

Statické zatížení zmíněné v parametrech je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

K tomuto výrobku si můžete přobjednat speciální [protiskluzovou podložku](#).

Selected variant

| | |
|-------------------------------------|---|
| Product name | Adjustable foot with foot ø123mm and holes for anchoring, PA+GF-stainless steel |
| Product code | 14624 |
| Height without washer H (mm) | 233 |
| Pitch K (mm) | 87 |
| SW key | 26 |
| Height with washer H1 (mm) | 236 |
| Foot height G (mm) | 37 |
| Screw length B (mm) | 175 |
| Thread F | M30 |
| Foot diameter D (mm) | 123 |
| Hole diameter L (mm) | 12,5 |
| Static load (N) | 35000 |
| Height A (mm) | 58 |

Variants

| Product name | Product code | QTY | Height without washer H (mm) | Pitch K (mm) | SW key | Height with washer H1 (mm) | Foot height G (mm) | Screw length B (mm) | Thread F | Foot diameter D (mm) | Hole diameter L (mm) | Static load (N) | Height A (mm) |
|--------------|--------------|-----|------------------------------|--------------|--------|----------------------------|--------------------|---------------------|----------|----------------------|----------------------|-----------------|---------------|
| | | | | | | | | | | | | | |

| | | | | | | | | | | | | | |
|---|-------|---|-----|----|----|-----|----|-----|-----|-----|------|-------|----|
| Adjustable foot with foot ø123mm and holes for anchoring, PA+GF-stainless steel | 14624 | 0 | 233 | 87 | 26 | 236 | 37 | 175 | M30 | 123 | 12,5 | 35000 | 58 |
| Adjustable foot with foot ø123mm and holes for anchoring, PA+GF-stainless steel | 13940 | 0 | 107 | 87 | 20 | 110 | 37 | 50 | M16 | 123 | 12,5 | 35000 | 57 |
| Adjustable foot with foot ø123mm and holes for anchoring, PA+GF-stainless steel | 13941 | 0 | 157 | 87 | 20 | 160 | 37 | 100 | M16 | 123 | 12,5 | 35000 | 57 |
| Adjustable foot with foot ø123mm and holes for anchoring, PA+GF-stainless steel | 13942 | 0 | 207 | 87 | 20 | 210 | 37 | 150 | M16 | 123 | 12,5 | 35000 | 57 |

| | | | | | | | | | | | | | |
|---|-------|---|-----|----|----|-----|----|-----|-----|-----|------|-------|----|
| Adjustable foot with foot ø123mm and holes for anchoring, PA+GF-stainless steel | 13943 | 0 | 257 | 87 | 20 | 260 | 37 | 200 | M16 | 123 | 12,5 | 35000 | 57 |
| Adjustable foot with foot ø123mm and holes for anchoring, PA+GF-stainless steel | 14424 | 0 | 132 | 87 | 20 | 135 | 37 | 75 | M20 | 123 | 12,5 | 35000 | 57 |
| Adjustable foot with foot ø123mm and holes for anchoring, PA+GF-stainless steel | 14425 | 0 | 157 | 87 | 20 | 160 | 37 | 100 | M20 | 123 | 12,5 | 35000 | 57 |
| Adjustable foot with foot ø123mm and holes for anchoring, PA+GF-stainless steel | 14426 | 0 | 192 | 87 | 20 | 185 | 37 | 125 | M20 | 123 | 12,5 | 35000 | 57 |

| | | | | | | | | | | | | | |
|---|-------|---|-----|----|----|-----|----|-----|-----|-----|------|-------|----|
| Adjustable foot with foot ø123mm and holes for anchoring, PA+GF-stainless steel | 14427 | 0 | 207 | 87 | 20 | 210 | 37 | 150 | M20 | 123 | 12,5 | 35000 | 57 |
| Adjustable foot with foot ø123mm and holes for anchoring, PA+GF-stainless steel | 14428 | 0 | 232 | 87 | 20 | 235 | 37 | 175 | M20 | 123 | 12,5 | 35000 | 57 |
| Adjustable foot with foot ø123mm and holes for anchoring, PA+GF-stainless steel | 14429 | 0 | 257 | 87 | 20 | 260 | 37 | 200 | M20 | 123 | 12,5 | 35000 | 57 |
| Adjustable foot with foot ø123mm and holes for anchoring, PA+GF-stainless steel | 14430 | 0 | 282 | 87 | 20 | 285 | 37 | 225 | M20 | 123 | 12,5 | 35000 | 57 |