

- **Materiál patka:** termoplast se skleněnými vlákny
- **Materiál šroub:** nerezová ocel
- **Barva patky:** černá

Statické zatížení, zmíněné níže v parametrech, je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

K tomuto výrobku si můžete přiojednat [speciální protiskluzovou podložku](#).

Selected variant

Product name	Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel
Product code	14410
Pitch K (mm)	87
Static load (N)	35000
Foot height G (mm)	37
Height with washer H1 (mm)	285
Screw length B (mm)	225
Height A (mm)	57
Height without washer H (mm)	282
Thread F	M20
SW key	20
Foot diameter D (mm)	123
Hole diameter L (mm)	12,5

Variants

Product name	Product code	QTY	Pitch K (mm)	Static load (N)	Foot height G (mm)	Height with washer H1 (mm)	Screw length B (mm)	Height A (mm)	Height without washer H (mm)	Thread F	SW key	Foot diameter D (mm)	Hole diameter L (mm)

Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel	13925	0	87	35000	37	110	50	57	107	M16	20	123	12,5
Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel	13926	0	87	35000	37	160	100	57	157	M16	20	123	12,5
Adjustable leg with foot ø123 mm and holes for anchoring, PA+GF-steel	13927	0	87	35000	37	210	150	57	207	M16	20	123	12,5
Nastavitelná noha s pátkou ø123 mm a otvory pro kotvení, PA+GF-ocel'	13928	0	87	35000	37	260	200	57	257	M16	20	123	12,5
Adjustable foot with with foot ø123 mm and holes for anchoring, PA+GF-steel	14404	0	87	35000	37	135	75	57	132	M20	20	123	12,5
Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel	14405	0	87	35000	37	160	100	57	157	M20	20	123	12,5

Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel	14406	0	87	35000	37	185	125	57	192	M20	20	123	12,5
Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel	14407	0	87	35000	37	210	150	57	207	M20	20	123	12,5
Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel	14408	0	87	35000	37	235	175	57	232	M20	20	123	12,5
Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel	14409	0	87	35000	37	260	200	57	257	M20	20	123	12,5
Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel	14410	0	87	35000	37	285	225	57	282	M20	20	123	12,5