

- **Foot material:** Thermoplastic with glass fibers
- **Screw material:** Stainless steel
- **Foot color:** Black

The static load mentioned in the parameters is calculated on the center of the screw. In the case of vibrations or dynamic loads, these values are reduced.

You can order a special [protišmiková podloska](#) for this product.

## Selected variant

<b>Product name</b>	Adjustable foot with foot $\varnothing$ 123mm and holes for anchoring, PA+GF-stainless steel
<b>Product code</b>	14424
<b>Height without washer H (mm)</b>	132
<b>Pitch K (mm)</b>	87
<b>SW key</b>	20
<b>Height with washer H1 (mm)</b>	135
<b>Foot height G (mm)</b>	37
<b>Screw length B (mm)</b>	75
<b>Thread F</b>	M20
<b>Foot diameter D (mm)</b>	123
<b>Hole diameter L (mm)</b>	12,5
<b>Static load (N)</b>	35000
<b>Height A (mm)</b>	57

## Variants

Product name	Product code	QTY	Height without washer H (mm)	Pitch K (mm)	SW key	Height with washer H1 (mm)	Foot height G (mm)	Screw length B (mm)	Thread F	Foot diameter D (mm)	Hole diameter L (mm)	Static load (N)	Height A (mm)
--------------	--------------	-----	------------------------------	--------------	--------	----------------------------	--------------------	---------------------	----------	----------------------	----------------------	-----------------	---------------

Adjustable foot with foot o123mm and holes for anchoring, PA+GF-stainless steel	14624	0	233	87	26	236	37	175	M30	123	12,5	35000	58
Adjustable foot with foot o123mm and holes for anchoring, PA+GF-stainless steel	13940	0	107	87	20	110	37	50	M16	123	12,5	35000	57
Adjustable foot with foot o123mm and holes for anchoring, PA+GF-stainless steel	13941	0	157	87	20	160	37	100	M16	123	12,5	35000	57
Adjustable foot with foot o123mm and holes for anchoring, PA+GF-stainless steel	13942	0	207	87	20	210	37	150	M16	123	12,5	35000	57

Adjustable foot with foot o123mm and holes for anchoring, PA+GF-stainless steel	13943	0	257	87	20	260	37	200	M16	123	12,5	35000	57
Adjustable foot with foot o123mm and holes for anchoring, PA+GF-stainless steel	14424	0	132	87	20	135	37	75	M20	123	12,5	35000	57
Adjustable foot with foot o123mm and holes for anchoring, PA+GF-stainless steel	14425	0	157	87	20	160	37	100	M20	123	12,5	35000	57
Adjustable foot with foot o123mm and holes for anchoring, PA+GF-stainless steel	14426	0	192	87	20	185	37	125	M20	123	12,5	35000	57

Adjustable foot with foot o123mm and holes for anchoring, PA+GF-stainless steel	14427	0	207	87	20	210	37	150	M20	123	12,5	35000	57
Adjustable foot with foot o123mm and holes for anchoring, PA+GF-stainless steel	14428	0	232	87	20	235	37	175	M20	123	12,5	35000	57
Adjustable foot with foot o123mm and holes for anchoring, PA+GF-stainless steel	14429	0	257	87	20	260	37	200	M20	123	12,5	35000	57
Adjustable foot with foot o123mm and holes for anchoring, PA+GF-stainless steel	14430	0	282	87	20	285	37	225	M20	123	12,5	35000	57