

- **Foot material:** glass-fiber reinforced thermoplastic
- **Screw material:** stainless steel
- **Foot color:** black

The static load, mentioned below in the parameters, is calculated at the center of the screw. In the case of vibrations or dynamic loads, these values are reduced.

You can order a [special anti-slip pad](#) for this product.

Selected variant

Product name	Adjustable foot with foot ø40mm, PA+GF-stainless steel
Product code	13894
Height A (mm)	27
Screw length B (mm)	100
Height with washer H1 (mm)	130
Foot diameter D (mm)	40
Foot height G (mm)	16,5
Height without washer H (mm)	127
SW key	12
Thread F	M12
Static load (N)	10000

Variants

Product name	Product code	QTY	Height A (mm)	Screw length B (mm)	Height with washer H1 (mm)	Foot diameter D (mm)	Foot height G (mm)	Height without washer H (mm)	SW key	Thread F	Static load (N)
Adjustable foot with foot ø40mm, PA+GF-stainless steel	13889	0	27	100	130	40	16,5	127	12	M10	10000

Product name	Product code	QTY	Height A (mm)	Screw length B (mm)	Height with washer H1 (mm)	Foot diameter D (mm)	Foot height G (mm)	Height without washer H (mm)	SW key	Thread F	Static load (N)
Adjustable foot with foot o40mm, PA+GF-stainless steel	13890	6	27	125	155	40	16,5	152	12	M10	10000
Adjustable foot with foot o40mm, PA+GF-stainless steel	13893	4	27	75	105	40	16,5	102	12	M12	10000
Adjustable foot with foot o40mm, PA+GF-stainless steel	13894	131	27	100	130	40	16,5	127	12	M12	10000
Adjustable foot with foot o40mm, PA+GF-stainless steel	13895	6	27	125	155	40	16,5	152	12	M12	10000
Adjustable foot with foot o40mm, PA+GF-stainless steel	13882	0	27	25	55	40	16,5	52	12	M8	10000
Adjustable foot with foot o40mm, PA+GF-stainless steel	13883	1	27	50	80	40	16,5	77	12	M8	10000
Adjustable foot with foot o40mm, PA+GF-stainless steel	13884	2	27	75	105	40	16,5	102	12	M8	10000

Product name	Product code	QTY	Height A (mm)	Screw length B (mm)	Height with washer H1 (mm)	Foot diameter D (mm)	Foot height G (mm)	Height without washer H (mm)	SW key	Thread F	Static load (N)
Adjustable foot with foot o40mm, PA+GF-stainless steel	13885	131	27	100	130	40	16,5	127	12	M8	10000
Adjustable foot with foot o40mm, PA+GF-stainless steel	13886	5	27	25	55	40	16,5	52	12	M10	10000
Nastavitelná noha s pátkou o40mm, PA+GF-nerez	13887	11	27	50	80	40	16,5	77	12	M10	10000
Adjustable foot with foot o40mm, PA+GF-stainless steel	13888	6	27	75	105	40	16,5	102	12	M10	10000
Adjustable foot with foot o40mm, PA+GF-stainless steel	13891	0	27	25	55	40	16,5	52	12	M12	10000
Adjustable leg with foot o40mm, PA+GF-stainless steel	13892	0	27	50	80	40	16,5	77	12	M12	10000