

Plastic connectors can significantly replace welded joints. They are indispensable, especially for anodized profiles.

The steel core in the plastic connector significantly strengthens the profile connection. These connectors are used in the construction of shelving structures, stands, etc.

Connectors with a steel core and without a core can be combined, e.g. in a shelving assembly - the upper shelf, where there is no such load, connectors with a metal core may not be needed, but cheaper plastic connectors without a core can be used.

Connectors with a steel core are very often used in the construction of aquarium walls due to their variability and strength.

## Selected variant

<b>Product name</b>	Square yak coupling, "Star", black
<b>Product code</b>	27430
<b>Height H (mm)</b>	52
<b>Wall thickness T (mm)</b>	1,5
<b>Side A (mm)</b>	25
<b>Steel reinforcement</b>	+

## Variants

Product name	Product code	QTY	Height H (mm)	Wall thickness T (mm)	Side A (mm)	Steel reinforcement
Square coupling of jacks, "Star", black	27426	10	36	1,5	20	-
Square coupling, "Star", black	27427	9	52	1,5	25	-
Square yak coupling, "Star", black	27430	5	52	1,5	25	+
Square jack coupling, "Star", black	27429	6	36	1,5	20	+
Spojka jaklov štvorcová, "Hviezda", čierna	27428	9	47	2	30	-
Jaklov coupling square, "Star", black	27431	6	47	2	30	+