

- **Materiál tělo:** nerezová ocel
- **Materiál kulička:** nerezová ocel
- **Barva:** stříbrná

Zvýšená zátěž.

Selected variant

| | |
|------------------------------|--|
| Product name | Sprung ball lock screw, for Allen key, stainless steel, increased strength |
| Product code | 14890 |
| I3 | 1,5 |
| N2 | 73 |
| Weight (g) | 3,6 |
| Length L (mm) | 16 |
| Thread D | M8 |
| N1 | 47 |
| Ball diameter D1 (mm) | 5 |
| Y (mm) | 4 |

Variants

| Product name | Product code | QTY | I3 | N2 | Weight (g) | Length L (mm) | Thread D | N1 | Ball diameter D1 (mm) | Y (mm) |
|---|--------------|-----|-----|----|------------|---------------|----------|----|-----------------------|--------|
| Spring-loaded locking screw with ball, for hex, stainless steel, increased strength | 14886 | 0 | 0,5 | 7 | 0,3 | 9 | M3 | 5 | 1,5 | 1,5 |
| Aretační skrutka s guličkou odpružená, na imbus, nerez, zvětšená síla | 14887 | 0 | 0,8 | 22 | 0,5 | 10 | M4 | 12 | 2,5 | 2 |
| Locking screw with spring-loaded ball, for hex, stainless steel, increased strength | 14888 | 11 | 0,9 | 30 | 1,3 | 14 | M5 | 19 | 3 | 3 |

| Product name | Product code | QTY | I3 | N2 | Weight (g) | Length L (mm) | Thread D | N1 | Ball diameter D1 (mm) | Y (mm) |
|--|--------------|-----|-----|-----|------------|---------------|----------|-----|-----------------------|--------|
| Sprung ball lock screw, for Allen, stainless steel, increased force | 14889 | 0 | 1 | 40 | 1,8 | 15 | M6 | 28 | 3,5 | 3 |
| Sprung ball lock screw, for Allen key, stainless steel, increased strength | 14890 | 15 | 1,5 | 73 | 3,6 | 16 | M8 | 47 | 5 | 4 |
| Locking screw M10x23mm with ball spring-loaded on hex increased strength stainless steel | 14891 | 0 | 2 | 100 | 6 | 23 | M10 | 66 | 6 | 5 |
| Spring-loaded ball lock screw, Allen key, stainless steel, increased strength | 14892 | 0 | 2,5 | 120 | 13 | 26 | M12 | 66 | 8 | 6 |
| Locking screw with spring-loaded ball, for hex, stainless steel, increased force | 14893 | 0 | 3,5 | 180 | 32 | 33 | M16 | 90 | 10 | 8 |
| Sprung ball lock screw, for hex, stainless steel, increased strength | 14894 | 0 | 4,5 | 240 | 63 | 43 | M20 | 115 | 12 | 10 |
| Spring-loaded ball lock screw, for Allen key, stainless steel, increased strength | 14895 | 0 | 5,5 | 270 | 98 | 48 | M24 | 130 | 15 | 12 |