

- **Foot material:** Thermoplastic with glass fibers
- **Screw material:** Galvanized steel
- **Foot color:** Black

The static load, mentioned below in the parameters, is calculated at the center of the screw. These values are reduced in the event of vibrations or dynamic loads.

You can order a [special anti-slip pad](#) for this product.

Selected variant

Product name	Adjustable foot with foot o40mm, PA+GF-steel
Product code	13867
Thread F	M10
Height A (mm)	27
Height with washer H1 (mm)	55
Foot diameter D (mm)	40
SW key	12
Screw length B (mm)	25
Static load (N)	10000
Foot height G (mm)	16,5
Height without washer H (mm)	52

Variants

Product name	Product code	QTY	Thread F	Height A (mm)	Height with washer H1 (mm)	Foot diameter D (mm)	SW key	Screw length B (mm)	Static load (N)	Foot height G (mm)	Height without washer H (mm)
Adjustable foot with foot o40mm, PA+GF-steel	13863	0	M8	27	55	40	12	25	10000	16,5	52
Adjustable foot with foot o40mm, PA+GF-steel	13864	0	M8	27	80	40	12	50	10000	16,5	77

A components s.r.o.

Bohunická 493/81

619 00 Brno

Web: www.acomponents.cz

E-mail: info@acomponents.cz

Telefon: 511 188 963

Maloobchodní prodej

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.

Product name	Product code	QTY	Thread F	Height A (mm)	Height with washer H1 (mm)	Foot diameter D (mm)	SW key	Screw length B (mm)	Static load (N)	Foot height G (mm)	Height without washer H (mm)
Nastavitelná noha s pätkou o40mm, PA+GF-ocel'	13865	0	M8	27	105	40	12	75	10000	16,5	102
Adjustable foot with foot o40mm, PA+GF-steel	13866	0	M8	27	130	40	12	100	10000	16,5	127
Adjustable foot with foot o40mm, PA+GF-steel	13867	0	M10	27	55	40	12	25	10000	16,5	52
Adjustable foot with foot o40mm, PA+GF-steel	13868	7	M10	27	80	40	12	50	10000	16,5	77
Adjustable foot with foot o40mm, PA+GF-steel	13869	35	M10	27	105	40	12	75	10000	16,5	102
Adjustable foot with foot o40mm, PA+GF-steel	13875	1	M10	27	130	40	12	100	10000	16,5	127
Adjustable foot with foot o40mm, PA+GF-steel	13876	4	M10	27	155	40	12	125	10000	16,5	152
Adjustable foot with foot o40 mm, PA+GF-steel	13877	0	M12	27	55	40	12	25	10000	16,5	52
Adjustable foot with foot o40mm, PA+GF-steel	13878	1	M12	27	80	40	12	50	10000	16,5	77

Product name	Product code	QTY	Thread F	Height A (mm)	Height with washer H1 (mm)	Foot diameter D (mm)	SW key	Screw length B (mm)	Static load (N)	Foot height G (mm)	Height without washer H (mm)
Adjustable foot with foot ø40mm, PA+GF-steel	13879	0	M12	27	105	40	12	75	10000	16,5	102
Adjustable foot with foot ø40mm, PA+GF-steel	13880	1	M12	27	130	40	12	100	10000	16,5	127
Adjustable foot with foot ø40mm, PA+GF-steel	13881	0	M12	27	155	40	12	125	10000	16,5	152