

- **Materiál:** termoplast se skleněnými vlákny
- **Barva:** matná černá
- **Speciální barvy na vyžádání:** červená RAL 3000, oranžová RAL 2004, bílá RAL 9010, šedá RAL 7031

Pro upevnění je zespodu slepé mosazné pouzdro s vnitřním závitem.

Při dodržení minimálního množství je možné nechat vyvrtat otvor se specifickým rozměrem.

## Selected variant

<b>Product name</b>	Bridge handle with internal thread closed, PA+GF
<b>Product code</b>	0
<b>Width E (mm)</b>	28
<b>Height F (mm)</b>	51
<b>Internal height C (mm)</b>	42
<b>Length A (mm)</b>	200
<b>Pitch B (mm)</b>	179
<b>Thread D</b>	M10
<b>Thread depth H (mm)</b>	13
<b>Weight (g)</b>	101

## Variants

Product name	Product code	QTY	Width E (mm)	Height F (mm)	Internal height C (mm)	Length A (mm)	Pitch B (mm)	Thread D	Thread depth H (mm)	Weight (g)
Bridge handle with internal thread closed, PA+GF	28722	2	28	51	42	200	179	M8	9	101
Bridge handle with internal thread closed, PA+GF	12557	10	26	37	29	121	105	M5	9	46

Product name	Product code	QTY	Width E (mm)	Height F (mm)	Internal height C (mm)	Length A (mm)	Pitch B (mm)	Thread D	Thread depth H (mm)	Weight (g)
Bridge handle with internal thread closed, PA+GF	12558	11	26	37	29	121	105	M6	9	48
Bridge handle with internal thread closed, PA+GF	12559	7	26	40	32	133	110	M5	9	58
Bridge handle with internal thread closed, PA+GF	12560	10	26	40	32	133	110	M6	9	60
Madlo mostové s vnitřním závitem uzatvorené, PA+GF	12561	12	26	40	32	133	117	M5	9	57
Universal protective caps, LDPE, yellow	12562	12	26	40	32	133	117	M6	9	59
Bridge handle with internal thread closed, PA+GF	12563	10	26	40	32	133	117	M8	9	61
Bridge handle with internal thread closed, PA+GF	29041	4	27	45	37	169	150	M8	9	76
Bridge handle with internal thread closed, PA+GF	29047	8	28	51	42	200	179	M10	13	101