

The perforated hose clamp has a thread formed by holes in the strip.

A clamp with a strip width of 12 mm has a destructive tightening torque of up to 15 Nm, which is approximately 3 times more than classic W1 hose clamps, which have a thread pressed into the strip.

The more durable the hose, the greater the tightening torque we can use.

Soft hoses cause the clamp to jump when tightened - the strip bends into the pliable material.

The clamping ranges of the clamp are from 6 to 230 mm in diameter.

For larger clamping ranges, an endless strip is intended.

- **Material:** galvanized steel

Zvolená varianta

Název produktu	Hadicová spona perforovaná, W1, 84-108
Kód	0
Šířka (mm)	12
Průměr (mm)	84-108

Varianty produktu

Název produktu	Kód	QTY	Šířka (mm)	Průměr (mm)
Hadicová spona perforovaná, W1, 6-16	00184	19	8	6-16
Hadicová spona perforovaná, W1, 11-20	00185	0	8	11-20
Hadicová spona perforovaná, W1, 14-27	00187	0	12	14-27
Hadicová spona perforovaná, W1, 13-25	00186	0	8	13-25
Hadicová spona perforovaná, W1, 21-38	00188	8	12	21-38
Hadicová spona perforovaná, W1, 27-51	00189	0	12	27-51
Hadicová spona perforovaná, W1, 40-63	00190	0	12	40-63
Hadicová spona perforovaná, W1, 52-76	00191	0	12	52-76
Hadicová spona perforovaná, W1, 84-108	00193	0	12	84-108
Hadicová spona perforovaná, W1, 65-89	00192	1	12	65-89
Hadicová spona perforovaná, W1, 105-127	00194	17	12	105-127
Hadicová spona perforovaná, W1, 130-152	00195	0	12	130-152

Název produktu	Kód	QTY	Šířka (mm)	Průměr (mm)
Hadicová spona perforovaná, W1, 178-203	00197	0	12	178-203
Hadicová spona perforovaná, W1, 156-178	00196	0	12	156-178
Hadicová spona perforovaná, W1, 203-230	00198	0	12	203-230

A components s.r.o.

Bohunická 493/81

619 00 Brno

Web: www.acomponents.czE-mail: info@acomponents.cz

Telefon: 511 188 963

Maloobchodní prodej

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.