

- **Material:** stainless steel
- **Color:** silver

The mentioned static load is calculated on the center of the screw. These values are lower in the case of vibrations or dynamic loads.

This system is developed for use in dairies, pharmaceutical and food industries, and factories that are subject to the strictest hygiene regulations.

The housing is equipped with a seal that, by its adhesion to the smooth surface of the screw, ensures that dirt does not enter.

USDA ORGANIC Certificate

USDA Organic is the American national form of certification awarded according to criteria for organic agriculture.

The goal of this federal organization is to support trade, agricultural organic production and rural communities, protect the environment and ensure food safety.

Selected variant

Product name	Adjustable foot for clean operation and pressed vulcan. foot, stainless steel
Product code	14202
Static load (N)	20000
Height H1 (mm)	243
Height H2 (mm)	178
SW key	17
Height B (mm)	200
Foot height G (mm)	30
Foot diameter D (mm)	123
Thread F	M20
Diameter D1 (mm)	30
Height A (mm)	43
Stroke adjustment (mm)	65

Variants

A components s.r.o.

Bohunická 493/81

619 00 Brno

Web: www.acomponents.cz

E-mail: info@acomponents.cz

Telefon: 511 188 963

Maloobchodní prodej

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.

Product name	Product code	QTY	Static load (N)	Height H1 (mm)	Height H2 (mm)	SW key	Height B (mm)	Foot height G (mm)	Foot diameter D (mm)	Thread F	Diameter D1 (mm)	Height A (mm)	Stroke adjust (mm)
Adjustable foot for clean operation with pressed vulcan. foot, stainless steel	14194	0	12000	162	97	17	125	24	85	M16	24	37	40
Adjustable foot for clean operation with pressed vulcan. foot, stainless steel	14195	5	12000	187	122	17	150	24	85	M16	24	37	65
Adjustable foot for clean operation with pressed vulcanized foot, stainless steel	14196	0	12000	187	12	17	150	24	85	M20	30	37	65
Adjustable leg for clean operation with pressed vulcan. foot, stainless steel	14197	0	12000	237	172	17	200	24	85	M20	30	37	65

Product name	Product code	QTY	Static load (N)	Height H1 (mm)	Height H2 (mm)	SW key	Height B (mm)	Foot height G (mm)	Foot diameter D (mm)	Thread F	Diameter D1 (mm)	Height A (mm)	Stroke adjust (mm)
Adjustable foot for clean operation with pressed vulcan. foot, stainless steel	14198	0	20000	193	128	17	150	30	123	M16	24	43	65
Adjustable foot for clean operation with pressed vulcanized foot foot, stainless steel	14199	0	20000	193	128	17	150	30	123	M20	30	43	65
Adjustable foot for cleanrooms with pressed vulcan. foot, stainless steel	14200	0	20000	194	129	20	150	30	123	M24	35	43	65
Adjustable foot for cleanrooms with pressed vulcanized foot, stainless steel	14201	0	20000	195	130	26	150	30	123	M30	42	43	65

Product name	Product code	QTY	Static load (N)	Height H1 (mm)	Height H2 (mm)	SW key	Height B (mm)	Foot height G (mm)	Foot diameter D (mm)	Thread F	Diameter D1 (mm)	Height A (mm)	Stroke adjust (mm)
Adjustable foot for clean operation and pressed vulcan. foot, stainless steel	14202	0	20000	243	178	17	200	30	123	M20	30	43	65
Adjustable foot for clean operation with pressed vulcanized foot, stainless steel	14203	0	20000	244	179	20	200	30	123	M24	35	43	65
Nastavitelná noha pro čisté převádzkay s lisovanou vulkan. pätkou, nerez	14204	0	20000	245	180	26	200	30	123	M30	42	43	65