

- **Materiál patka:** galvanizovaná ocel + vulkanizovaná guma NBR 80 Shore
- **Materiál šroub:** galvanizovaná ocel C40
- **Barva patky:** stříbrná + černá

Zmíněné statické zatížení je počítáno na střed šroubu. Při vibracích či dynamickém zatížení jsou tyto hodnoty poníženy.

## Selected variant

|                             |  |
|-----------------------------|--|
| <b>Product name</b>         | Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel |
| <b>Product code</b>         | 14452  |
| <b>SW key</b>               | 14   |
| <b>Height A (mm)</b>        | 35   |
| <b>Foot height G (mm)</b>   | 25   |
| <b>Pitch I (mm)</b>         | 54   |
| <b>Foot diameter D (mm)</b> | 80   |
| <b>Static load (N)</b>      | 10000  |
| <b>Screw length B (mm)</b>  | 100  |
| <b>Height H (mm)</b>        | 135  |
| <b>Thread F</b>             | M12  |

## Variants

| Product name  | Product code | QTY | SW key | Height A (mm) | Foot height G (mm) | Pitch I (mm) | Foot diameter D (mm) | Static load (N) | Screw length B (mm) | Height H (mm) | Thread F |
|---|--------------|-----|--------|---------------|--------------------|--------------|----------------------|-----------------|---------------------|---------------|----------|
| Adjustable leg with vulcanized foot ø80 mm and eyelet, galvanized steel | 14449        | 11  | 14     | 35            | 25                 | 54           | 80                   | 10000           | 50                  | 85            | M10      |

| Product name  | Product code | QTY | SW key | Height A (mm) | Foot height G (mm) | Pitch I (mm) | Foot diameter D (mm) | Static load (N) | Screw length B (mm) | Height H (mm) | Thread F |
|---|--------------|-----|--------|---------------|--------------------|--------------|----------------------|-----------------|---------------------|---------------|----------|
| Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel          | 14450        | 13  | 14     | 35            | 25                 | 54           | 80                   | 10000           | 100                 | 135           | M10      |
| Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel          | 14451        | 0   | 14     | 35            | 25                 | 54           | 80                   | 10000           | 50                  | 85            | M12      |
| Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel          | 14452        | 4   | 14     | 35            | 25                 | 54           | 80                   | 10000           | 100                 | 135           | M12      |
| Pipe covers Type 1, LDPE, natural, yellow, black, red, white                | 14453        | 2   | 14     | 35            | 25                 | 54           | 80                   | 10000           | 150                 | 185           | M12      |
| Adjustable foot with vulcan. with foot ø80 mm and eyelet, galvanized. steel | 14454        | 0   | 14     | 35            | 25                 | 54           | 80                   | 10000           | 50                  | 85            | M14      |
| Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel          | 14455        | 0   | 14     | 35            | 25                 | 54           | 80                   | 10000           | 100                 | 135           | M14      |

| Product name   | Product code | QTY | SW key | Height A (mm) | Foot height G (mm) | Pitch I (mm) | Foot diameter D (mm) | Static load (N) | Screw length B (mm) | Height H (mm) | Thread F |
|--|--------------|-----|--------|---------------|--------------------|--------------|----------------------|-----------------|---------------------|---------------|----------|
| Adjustable foot with vulcan. foot ø80 mm and eyelet, galvanised steel    | 14456        | 0   | 14     | 35            | 25                 | 54           | 80                   | 10000           | 150                 | 185           | M14      |
| Adjustable foot with vulcanized foot ø80 mm and eye, galvanized steel    | 14457        | 5   | 14     | 35            | 25                 | 54           | 80                   | 10000           | 50                  | 85            | M16      |
| Adjustable foot with vulcan. foot ø80 mm and eye, galvanised steel       | 14458        | 13  | 14     | 35            | 25                 | 54           | 80                   | 10000           | 100                 | 135           | M16      |
| Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel       | 14459        | 6   | 14     | 35            | 25                 | 54           | 80                   | 10000           | 150                 | 185           | M16      |
| Adjustable foot with vulcan. with foot ø80 mm and eye, galvanized steel  | 14460        | 2   | 14     | 35            | 25                 | 54           | 80                   | 10000           | 200                 | 235           | M16      |
| Adjustable foot with vulcanized foot ø80 mm and eyelet, galvanized steel | 14461        | 5   | 20     | 36            | 25                 | 54           | 80                   | 10000           | 75                  | 111           | M20      |

| Product name  | Product code | QTY | SW key | Height A (mm) | Foot height G (mm) | Pitch I (mm) | Foot diameter D (mm) | Static load (N) | Screw length B (mm) | Height H (mm) | Thread F |
|---|--------------|-----|--------|---------------|--------------------|--------------|----------------------|-----------------|---------------------|---------------|----------|
| Adjustable foot with vulcanized foot ø80 mm and eye, galvanized steel | 14462        | 0   | 20     | 36            | 25                 | 54           | 80                   | 10000           | 100                 | 136           | M20      |
| Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel    | 14463        | 0   | 20     | 36            | 25                 | 54           | 80                   | 10000           | 150                 | 186           | M20      |
| Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel    | 14464        | 0   | 20     | 36            | 25                 | 54           | 80                   | 10000           | 200                 | 236           | M20      |
| Adjustable foot with vulcanized foot ø80 mm and eye, galvanized steel | 14465        | 0   | 24     | 36            | 25                 | 54           | 80                   | 10000           | 75                  | 111           | M24      |
| Adjustable foot with vulcan. foot ø80 mm and eye, galvanized steel    | 14466        | 10  | 24     | 36            | 25                 | 54           | 80                   | 10000           | 100                 | 136           | M24      |
| Adjustable foot with vulcanized foot ø80 mm and eye, galvanized steel | 14467        | 0   | 24     | 36            | 25                 | 54           | 80                   | 10000           | 150                 | 186           | M24      |

| Product name  | Product code | QTY | SW key | Height A (mm) | Foot height G (mm) | Pitch I (mm) | Foot diameter D (mm) | Static load (N) | Screw length B (mm) | Height H (mm) | Thread F |
|---|--------------|-----|--------|---------------|--------------------|--------------|----------------------|-----------------|---------------------|---------------|----------|
| Adjustable leg with vulcanized foot ø80 mm and eye, galvanized. steel | 14468        | 5   | 24     | 36            | 25                 | 54           | 80                   | 10000           | 200                 | 236           | M24      |

**A components s.r.o.**Bohunická 493/81  
619 00 BrnoWeb: [www.acomponents.cz](http://www.acomponents.cz)E-mail: [info@acomponents.cz](mailto:info@acomponents.cz)

Telefon: 511 188 963

**Maloobchodní prodej**

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.