

- **Foot material:** galvanized steel + vulcanized rubber NBR 80 Shore
- **Screw material:** galvanized steel C40
- **Foot color:** silver + black

The mentioned static load is calculated on the center of the screw. In case of vibrations or dynamic loads, these values are lower.

## Selected variant

|                             |  |
|-----------------------------|--|
| <b>Product name</b>         | Adjustable foot with vulcan. foot ø50 mm, galvanised steel |
| <b>Product code</b>         | 14311  |
| <b>Screw length B (mm)</b>  | 100  |
| <b>Foot diameter D (mm)</b> | 50   |
| <b>Height H (mm)</b>        | 129  |
| <b>Thread F</b>             | M16  |
| <b>SW key</b>               | 16   |
| <b>Foot height G (mm)</b>   | 19   |
| <b>Static load (N)</b>      | 4000   |
| <b>Height A (mm)</b>        | 29   |

## Variants

| Product name   | Product code | QTY | Screw length B (mm) | Foot diameter D (mm) | Height H (mm) | Thread F | SW key | Foot height G (mm) | Static load (N) | Height A (mm) |
|--|--------------|-----|---------------------|----------------------|---------------|----------|--------|--------------------|-----------------|---------------|
| Adjustable foot with vulcan. foot ø50 mm, galvanised steel | 14302        | 10  | 50                  | 50                   | 79            | M10      | 14     | 19                 | 4000            | 29            |
| Adjustable foot with vulcan. foot ø50 mm, galvanised steel | 14303        | 10  | 100                 | 50                   | 129           | M10      | 14     | 19                 | 4000            | 29            |

| Product name  | Product code | QTY | Screw length B (mm) | Foot diameter D (mm) | Height H (mm) | Thread F | SW key | Foot height G (mm) | Static load (N) | Height A (mm) |
|---|--------------|-----|---------------------|----------------------|---------------|----------|--------|--------------------|-----------------|---------------|
| Adjustable foot with vulcanized foot ø50 mm, galvanised steel | 14304        | 0   | 50                  | 50                   | 79            | M12      | 14     | 19                 | 4000            | 29            |
| Adjustable foot with vulcan. foot ø50 mm, galvanised steel    | 14305        | 4   | 100                 | 50                   | 129           | M12      | 14     | 19                 | 4000            | 29            |
| Adjustable foot with vulcan. foot ø50 mm, galvanised steel    | 14306        | 2   | 150                 | 50                   | 179           | M12      | 14     | 19                 | 4000            | 29            |
| Adjustable foot with vulcan. foot ø50 mm, galvanised. steel   | 14307        | 0   | 50                  | 50                   | 79            | M14      | 14     | 19                 | 4000            | 29            |
| Adjustable foot with vulcanized foot ø50 mm, galvanised steel | 14308        | 0   | 100                 | 50                   | 129           | M14      | 14     | 19                 | 4000            | 29            |
| Adjustable foot with vulcan. foot ø50 mm, galvanised. steel   | 14309        | 0   | 150                 | 50                   | 179           | M14      | 14     | 19                 | 4000            | 29            |
| Adjustable foot with vulcanized foot ø50 mm, galvanised steel | 14310        | 5   | 75                  | 50                   | 104           | M16      | 16     | 19                 | 4000            | 29            |
| Adjustable foot with vulcan. foot ø50 mm, galvanised steel    | 14311        | 10  | 100                 | 50                   | 129           | M16      | 16     | 19                 | 4000            | 29            |
| Adjustable foot with vulcan. foot ø50 mm, galvanised steel    | 14312        | 6   | 150                 | 50                   | 179           | M16      | 16     | 19                 | 4000            | 29            |

| Product name  | Product code | QTY | Screw length B (mm) | Foot diameter D (mm) | Height H (mm) | Thread F | SW key | Foot height G (mm) | Static load (N) | Height A (mm) |
|---|--------------|-----|---------------------|----------------------|---------------|----------|--------|--------------------|-----------------|---------------|
| Adjustable foot with vulcanized foot ø50 mm, galvanised steel | 14313        | 2   | 200                 | 50                   | 229           | M16      | 16     | 19                 | 4000            | 29            |