

- **Foot material:** thermoplastic with glass fibers
- **Screw material:** stainless steel
- **Foot color:** black

The static load, mentioned below in the parameters, is calculated on the center of the screw. In the case of vibrations or dynamic loads, these values are reduced.

You can additionally order [a special anti-slip pad](#) for this product.

Variants

| Product name | Product code | QTY | Pitch K (mm) | Static load (N) | Foot height G (mm) | Height with washer H1 (mm) | Screw length B (mm) | Height A (mm) | Height without washer H (mm) | Thread F | SW key | Foot diameter D (mm) | Hole diameter L (mm) |
|--|--------------|-----|--------------|-----------------|--------------------|----------------------------|---------------------|---------------|------------------------------|----------|--------|----------------------|----------------------|
| Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel | 13925 | 0 | 87 | 35000 | 37 | 110 | 50 | 57 | 107 | M16 | 20 | 123 | 12,5 |
| Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel | 13926 | 0 | 87 | 35000 | 37 | 160 | 100 | 57 | 157 | M16 | 20 | 123 | 12,5 |
| Adjustable leg with foot ø123 mm and holes for anchoring, PA+GF-steel | 13927 | 0 | 87 | 35000 | 37 | 210 | 150 | 57 | 207 | M16 | 20 | 123 | 12,5 |

| Product name | Product code | QTY | Pitch K (mm) | Static load (N) | Foot height G (mm) | Height with washer H1 (mm) | Screw length B (mm) | Height A (mm) | Height without washer H (mm) | Thread F | SW key | Foot diameter D (mm) | Hole diameter L (mm) |
|---|--------------|-----|--------------|-----------------|--------------------|----------------------------|---------------------|---------------|------------------------------|----------|--------|----------------------|----------------------|
| Nastavitelná noha s pátkou ø123 mm a otvory pro kotvení, PA+GF-ocel' | 13928 | 0 | 87 | 35000 | 37 | 260 | 200 | 57 | 257 | M16 | 20 | 123 | 12,5 |
| Adjustable foot with with foot ø123 mm and holes for anchoring, PA+GF-steel | 14404 | 0 | 87 | 35000 | 37 | 135 | 75 | 57 | 132 | M20 | 20 | 123 | 12,5 |
| Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel | 14405 | 0 | 87 | 35000 | 37 | 160 | 100 | 57 | 157 | M20 | 20 | 123 | 12,5 |
| Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel | 14406 | 0 | 87 | 35000 | 37 | 185 | 125 | 57 | 192 | M20 | 20 | 123 | 12,5 |
| Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel | 14407 | 0 | 87 | 35000 | 37 | 210 | 150 | 57 | 207 | M20 | 20 | 123 | 12,5 |

| Product name | Product code | QTY | Pitch K (mm) | Static load (N) | Foot height G (mm) | Height with washer H1 (mm) | Screw length B (mm) | Height A (mm) | Height without washer H (mm) | Thread F | SW key | Foot diameter D (mm) | Hole diameter L (mm) |
|--|--------------|-----|--------------|-----------------|--------------------|----------------------------|---------------------|---------------|------------------------------|----------|--------|----------------------|----------------------|
| Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel | 14408 | 0 | 87 | 35000 | 37 | 235 | 175 | 57 | 232 | M20 | 20 | 123 | 12,5 |
| Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel | 14409 | 0 | 87 | 35000 | 37 | 260 | 200 | 57 | 257 | M20 | 20 | 123 | 12,5 |
| Adjustable foot with foot ø123 mm and holes for anchoring, PA+GF-steel | 14410 | 0 | 87 | 35000 | 37 | 285 | 225 | 57 | 282 | M20 | 20 | 123 | 12,5 |

A components s.r.o.

 Bohunická 493/81
 619 00 Brno

 Web: www.acomponents.cz

 E-mail: info@acomponents.cz

Telefon: 511 188 963

Maloobchodní prodej

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.