

- **Foot material:** thermoplastic with glass fibers
- **Screw material:** galvanized steel
- **Foot color:** black

The static load, mentioned below in the parameters, is calculated on the center of the screw. In the case of vibrations or dynamic loads, these values are reduced.

You can additionally order [a special anti-slip pad](#) for this product.

Selected variant

Product name	Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel
Product code	13807
Height with washer H1 (mm)	116
Foot height G (mm)	27
Foot diameter D (mm)	83
Hole diameter L (mm)	8,5
Height A (mm)	38
Screw length B (mm)	75
Pitch K (mm)	55
Height without washer H (mm)	113
Thread F	M12
Static load (N)	15000
SW key	14

Variants

Product name	Product code	QTY	Height with washer H1 (mm)	Foot height G (mm)	Foot diameter D (mm)	Hole diameter L (mm)	Height A (mm)	Screw length B (mm)	Pitch K (mm)	Height without washer H (mm)	Thread F	Static load (N)	SW key
--------------	--------------	-----	----------------------------	--------------------	----------------------	----------------------	---------------	---------------------	--------------	------------------------------	----------	-----------------	--------

Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	28396	4	133	18	83	8,5	30	100	54	130	M16	16000	13
Adjustable foot with ø83mm foot and holes for anchoring, PA+GF-steel	14251	0	144	27	83	8,5	41	100	55	141	M20	20000	17
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13896	0	91	27	83	8,5	38	50	55	88	M16	20000	16
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13897	0	116	27	83	8,5	38	75	55	113	M16	20000	16
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13898	0	141	27	83	8,5	38	100	55	138	M16	20000	16
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13899	0	166	27	83	8,5	38	125	55	163	M16	20000	16

Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13900	0	191	27	83	8,5	38	150	55	188	M16	20000	16
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13901	0	216	27	83	8,5	38	175	55	213	M16	20000	16
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13902	0	241	27	83	8,5	38	200	55	238	M16	20000	16
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	14391	0	119	27	83	8,5	41	75	55	116	M20	20000	17
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	14392	0	169	27	83	8,5	41	125	55	166	M20	20000	17
Adjustable foot with foot ø83 mm and holes for anchoring, PA+GF-steel	14393	0	194	27	83	8,5	41	150	55	191	M20	20000	17

Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	14394	0	219	27	83	8,5	41	175	55	216	M20	20000	17
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	14395	0	244	27	83	8,5	41	200	55	241	M20	20000	17
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	14396	0	269	27	83	8,5	41	225	55	266	M20	20000	17
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	29226	1	-	20	103	12,5	32	100	73	132	M16	18000	13
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13802	0	91	27	83	8,5	38	50	55	88	M10	15000	14
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13803	0	116	27	83	8,5	38	75	55	113	M10	15000	14

Adjustable foot with ø83mm foot and holes for anchoring, PA+GF-steel	13804	0	141	27	83	8,5	38	100	55	138	M10	15000	14
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13805	0	166	27	83	8,5	38	125	55	163	M10	15000	14
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13806	0	91	27	83	8,5	38	50	55	88	M12	15000	14
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13807	0	116	27	83	8,5	38	75	55	113	M12	15000	14
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13808	0	141	27	83	8,5	38	100	55	138	M12	15000	14
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13809	0	166	27	83	8,5	38	125	55	163	M12	15000	14

Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13810	0	91	27	83	8,5	38	50	55	88	M14	20000	14
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13811	0	116	27	83	8,5	38	75	55	113	M14	20000	14
Nastavitelná noha s pätkou ø83mm a otvory pro kotvení, PA+GF-ocel'	13812	0	141	27	83	8,5	38	100	55	138	M14	20000	14
Threaded sealing plugs Type 1, PA 6, yellow	13813	0	166	27	83	8,5	38	125	55	163	M14	20000	14
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13814	0	191	27	83	8,5	38	150	55	188	M14	20000	14
Adjustable foot with foot ø83mm and holes for anchoring, PA+GF-steel	13815	0	216	27	83	8,5	38	175	55	213	M14	20000	14