

Spiral suitable for protecting hydraulic pipes and their distribution.
Resists abrasion, impact, UV radiation, oil, ozone and very low temperatures.

- **Material:** HDPE
- **Temperature range of use:** -60°C - +100°C
- **Hardness:** 66 SHw 5
- **Density:** 0.96 gr/cc

Available in a combination of different colors.

Variants

Product name	Product code	QTY	Weight/1m (kg)	Outer diameter D (mm)	Climb P	ID inside diameter (mm)
Two-color protective spirals, HDPE	30585	0	0,06	16	10-11	13
Protective spirals, two-tone, HDPE	30586	0	0,10	20	18-19	16
Two-tone protective spirals, HDPE	30587	0	0,12	25	20-21	20
Two-color protective spirals, HDPE	30588	0	0,24	32	22-23	27
Two-tone protective spirals, HDPE	30590	0	0,45	50	29-31	43
Two-color protective spirals, HDPE	30589	0	0,30	40	25-26	34

A components s.r.o.

Bohunická 493/81

619 00 Brno

Web: www.acomponents.cz

E-mail: info@acomponents.cz

Telefon: 511 188 963

Maloobchodní prodej

Standardizované komponenty můžete objednávat také v našem e-shopu.

Skladové zboží expedujeme obvykle do 48 hodin od potvrzení objednávky.